Samson.



This non-slip, easy-care vinyl contains special inlaid mineral crystal particles in the wear layer for added traction on ramps, stairways, busy walkways and traditional wet areas like hospital bathrooms.



7386 Fynbos



7618 Edelweis



7767 Quagga

Drawing Inspiration
Offering a surface with superior anti-slip safety and grip for wheelchairs, trolleys and soles of shoes, Samson is designed to withstand excessive abrasion from heavy traffic.



Extended Specifications

Use Classification	34-43 (EN 685)	Heavy Commercial
Total Thickness	1.95mm	
Weight	2210g/m2	
Width	2m	
Roll Length	20Lm	
Wear Group	T (EN 649)	
Wear Resistance	≤ 2mm3 (EN 660.2)	
Static Electrical Propensity	< 2kV (EN 1815)	
Fire Rating	Bfl-s1 (EN 13501-1)	
Slip Resistance	R10 (DIN 51130)	
Dimensional Stability	≤ 0.4% (EN 434)	
Residual Indentation	≈ 0.1mm (EN 433)	
Thermal Conductivity	0.25W/(m.K) (EN 12524)	
Colour fastness	≥6° (EN 20105 - B02)	
Chemical Resistance	Yes (EN 423)	
Antibacterial & Fungicidal Treatment	Yes	
TVOC After 28 Days	<100µg/m3 (ISO 16000-6)	