B_

Accelerate




Extended Specifications


Use Classification	Heavy Commercial - 33 (EN 1307)
Construction	Tufted Multi Scroll Loop Pile
Product Description	Heavy Commercial SDN Tufted Loop Pile Bitumen Tile - SS
Recycled Content	Yarn - Stainproof SDX Eco (Certain Colours) Backing - EcoBac S3 (On Request)
Yarn Type	Stainproof SDX (Solution Dyed Nylon-6)
Pile Height	± 2 - 3.5mm
Total Thickness (NexBac SX)	± 5mm
Total Mass (NexBac SX)	± 3500g/m²**
Standard Tile Size	50x50cm***
Standard Backing Type	NexBac SX
Machine Gauge	1/10”
Stitches/10cm	60 (±1)
Fire Classification	2 (SANS 10177-4) Bfl-s1 (EN 13501) Class 1 (ASTM E 648-08)
Colour Fastness To:	
i) Light	8 (AATCC 16/ISO 105 B02)
ii) Rubbing (Change of Colour)	4/5 (AATCC 165/ISO 105 X 12)
iii) Rubbing (Staining)	5 (AATCC 165/ISO 105 X 12)
Electrostatic Propensity	≤ 2kV (ISO 6356/EN 1307)
Static Control	Permanent
Sound Absorption (NexBac SX)	aω 0.15 (EN ISO 354:2003)
Sound Insulation (NexBac SX)	ΔLw = 18dB (ISO 717-2)
Thermal Resistance (NexBac SX)	0.0638m².K/W (ISO 8302)
VOC Tested	Pass (GBCSA/GBCA)
Castor Chair Suitability	A: Intense Use (NF EN 985)
Guarantee	5 Years
Limited Wear Warranty	15 Years

B_

Edit




Calm
LRV: L=47.46 Y=16.37




Comfort
LRV: L=39.45 Y=10.92



Grounded
LRV: L=29.93 Y=6.21



Solid
LRV: L=35.87 Y=8.94



Strength
LRV: L=23.23 Y=3.87

Accelerate

The Pace of Pattern.











**Weighted Average
***Also available in 50x50cm EcoBac - S3 tiles, 25x100cm SX/EcoBac - S3 plank & 100x100cm SX/EcoBac - S3 tiles. As these custom offerings are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information on this. Belgotex Accelerate 25x100cm planks to be installed in the following directions: Herringbone, Ashlar, Random Ashlar & Colour Mix.

Bill of Quantities

- Belgotex Accelerate 50x50cm tiles are manufactured from Stainproof SDX (Solution Dyed nylon-6 for extreme conditions).
- This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex Accelerate 50x50cm & 100x100cm tiles to be installed in the following directions: Tessellated, Ashlar, Random Ashlar, Brick, Monolithic, Colour Mix & Random.
- Belgotex recommends the use of Carpet protector mats where castor wheels are used.
- Green Tag A level plus certification • 15 Yr Warranty & 5 Yr Guarantee • Made in South Africa

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd.
© BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.