

DESCRIPTION

- 8 or 15 keys microphone console to broadcast live or delayed messages: keypad with capacitive keys (each key corresponds to a zone and is equipped with a green LED to indicate the selection of the zone).
- 3 push-buttons to record (record with replay), to broadcast live or delayed.
- Built-in loud-speaker to listen to the message before broadcast.
- "Jingle" before broadcast of the message.
- Archiving of voice messages. A filed message can be used in a step of a program.

*SEP: Safety Emergency Procedures.

NORMS

- CEM 2004/108/CEE Directive and Low Voltage Directive 2006/95/CEE.
- EN 60950: Safety of information technology equipment.
- EN 55022: Radio disturbance of information technology equipment.
- EN 55024: Immunity of information technology equipment.

ELECTRICAL FEATURES

- **Power supply**..... PoE (Power over Ethernet).
- **Consumption**..... 8 W.
- **Sensitivity**..... -58dB ±2dB.
- **Number of keys**..... 8 or 15.

MECHANICAL FEATURES

- **Construction**..... LCD screen with 2 lines of characters:
 - Character size: 5 mm.
 - White characters on blue background.
 - Maximum number of characters per lines: 12.
- **Operating temperature range**..... 0° to +50°C.
- **Protection index**..... IP31.
- **Weight**..... 0.440 kg.
- **Dimensions of the base**..... L198 x H34/23 x D167 mm.
- **Gooseneck length (including the microphone)** 330 mm.

See the product page
>> www.bodet-time.com <<

REFERENCES

- 907 755..... Harmonys microphone - 8 keys
- 907 756..... Harmonys microphone - 15 keys



Dimensions in mm