








STEELWORX® 304 STAINLESS STEEL




| | | | | | |
|---|---|---|---|---|--|
|  |  |  |  |  |  |
|---|---|---|---|---|--|


SWL1010DUO







BERNA
Solid Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

| | |
|-----------------|---------|
| Rose: | 52 Dia. |
| Rose Thickness: | 7 |
| Projection: | 62 |
| Lever Length: | 136 |
| Bar: | 19 Dia. |

 **BSS/SSS**




| | | | | | |
|---|---|---|---|---|--|
|  |  |  |  |  |  |
|---|---|---|---|---|--|


SWL1121







BREEZE
Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

| | |
|-----------------|---------|
| Rose: | 52 Dia. |
| Rose Thickness: | 7 |
| Projection: | 64 |
| Lever Length: | 127 |

 **SSS**




| | | | | | |
|---|---|---|---|---|--|
|  |  |  |  |  |  |
|---|---|---|---|---|--|

SWL1122

BREMA
Solid Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

| | |
|-----------------|---------|
| Rose: | 52 Dia. |
| Rose Thickness: | 7 |
| Projection: | 64 |
| Lever Length: | 135 |

 **SSS**

Steelworx levers are supplied with bolt through fixings and should be used in conjunction with BTL's on P437 and Eurospec locks. For matching escutcheons SWL102/103 see P87. For matching bathroom turns SWT1016/1016i and SWT1025i see P87.