









Grade 316 Stainless Steel Levers on Screw on Rose



Product Code: SW18

STEELWORX® 316 STAINLESS STEEL

						
			BS EN 1906		FD30/40	FD120/240



SW10

STRAIGHT
Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose



Dimensions (mm):









Rose:	50 Dia.
Rose Thickness:	6
Projection:	65
Lever Length:	133
Bar:	16 Dia.


Variations:

SW12 Bar 19 Dia.

SW124 Sprung - Bar 19 Dia.

 **BSS**  **SSS**

							
				BS EN 1906		FD30/60	FD120/240



SW11

SAFETY
Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	50 Dia.
Rose Thickness:	6
Projection:	66
Lever Length:	140
Bar:	19 Dia.



Variations:

SW15 Bar 22 Dia.


SW122* Sprung - Bar 16 Dia.

SW123 Sprung - Bar 19 Dia.








SW127 Sprung - Bar 22 Dia.

 **BSS**  **SSS**


Steelworx levers are supplied with bolt through fixings and should be used in conjunction with BTL's on P437 and Eurospec locks. For matching escutcheons SW102-104 see P100. For matching bathroom turns SW105/i and 107/i see P100. SW10, SW15, SW122 and SW127 not available in BSS finish.

*  Does not apply to SW122.

STEELWORX® 316 STAINLESS STEEL

BS EN 1906
FD30/60
FD120/240



SW13

MITRED



Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose








Dimensions (mm):

Rose:	50 Dia.
Rose Thickness:	6
Projection:	66
Lever Length:	135
Bar:	19 Dia.


Variations:

SW125 Sprung - Bar 19 Dia.

 **BSS**  **SSS**

BS EN 1906
FD30/60
FD120/240



SW14

CURVED



Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):








Rose:	50 Dia.
Rose Thickness:	6
Projection:	67
Lever Length:	135
Bar:	19 Dia.


Variations:

SW126 Sprung - Bar 19 Dia.

 **BSS**  **SSS**

STEELWORX® 316 STAINLESS STEEL


			 BS EN 1906		 FD30/A0	 FD120/240	SW16
---	---	---	---	---	--	--	-------------











DESIGNER
Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	50 Dia.
Rose Thickness:	6
Projection:	70
Lever Length:	115

 **SSS**


			 BS EN 1906		 FD30/A0	 FD120/240	SW18
---	---	---	---	---	--	--	-------------



CARBON FIBRE
Lever on Round Bearing Rose - Solid
Concealed Fix 2 Part Screw-on-Rose








Dimensions (mm):


Rose:	50 Dia.
Rose Thickness:	6
Projection:	65
Lever Length:	124
Bar:	20 Dia.

 **SSS**

Steelworx levers are supplied with bolt through fixings and should be used in conjunction with BTL's on P437 and Eurospec locks. For matching escutcheons SW101-104 see P100. For matching bathroom turns SW105/i and 107/i see P8100.

STEELWORX® 316 STAINLESS STEEL

						
			BS EN 1906	25	FD30/60	FD120/240




SW19

DESIGNER
Lever on Round Bearing Rose - Solid Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	50 Dia.
Rose Thickness:	6
Projection:	64
Lever Length:	135

 **SSS**

						
			BS EN 1906	25	FD30/60	FD120/240



SW120









DESIGNER
Lever on Round Bearing Rose - Solid Concealed Fix 2 Part Screw-on-Rose


Dimensions (mm):

Rose:	50 Dia.
Rose Thickness:	6
Projection:	72
Lever Length:	124

 **SSS**

STEELWORX® 316 STAINLESS STEEL


							
---	---	---	---	---	---	---	---












SW140

DESIGN LEVER
Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):
 Rose: 50 Dia.
 Rose Thickness: 6
 Projection: 71
 Lever Length: 147

 **SSS**


							
---	---	---	---	---	---	---	---



SW141

DESIGN LEVER
Lever on Round Bearing Rose
Concealed Fix 2 Part Screw-on-Rose





Dimensions (mm):
 Rose: 50 Dia.
 Rose Thickness: 6
 Projection: 67
 Lever Length: 144





 **SSS**

Steelworx levers are supplied with bolt through fixings and should be used in conjunction with BTL's on P437 and Eurospec locks. For matching escutcheons SW102-104 see P100. For matching bathroom turns SW105/i and 107/i see P100.

STEELWORX® 316 STAINLESS STEEL

		SW102/3/4
	<p>ESCUTCHEON Concealed Fix 2 Part Screw-on-Rose</p> <p>Dimensions (mm): Rose: 50 Dia. Rose Thickness: 6</p> <p>SW102 Euro SW103 Lock SW104 Oval</p> <p> BSS  SSS</p>	

		SW105
	<p>THUMBTURN AND RELEASE Concealed Fix 2 Part Screw-on-Rose</p> <p>Dimensions (mm): Rose: 50 Dia. Rose Thickness: 6</p> <p>Variations: SW105i With Indicator</p> <p> BSS  SSS</p>	

		SW107
	<p>DESIGNER THUMBTURN AND RELEASE Concealed Fix 2 Part Screw-on-Rose</p> <p>Dimensions (mm): Rose: 50 Dia. Rose Thickness: 6</p> <p> BSS  SSS</p>	

LEVER ON ROSE ACCESSORIES



ALP5038

**1/2 SET FIXING PLATE
FOR BOLT THROUGH
FURNITURE**

Dimensions (mm):

Centres: 38



SP6T

TAYLOR SPINDLE

Dimensions (mm):

Spindle: 8

Length: 26

Variations:

SP6T1 7.6x25



SSS

Are you following us ?



www.carlislebrass.com