

STEELWORX® 304 STAINLESS STEEL

		 BS EN 1906		 FD30/A0	 FD120/240
---	---	---	---	--	---



SWL1168

PARIGI
Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	52 Dia.
Rose Thickness:	7
Projection:	62
Lever Length:	127

SSS

			 BS EN 1906		 FD30/A0	 FD120/240
---	---	---	---	---	--	---



SWL1190

NERA
Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	52 Dia.
Rose Thickness:	7
Projection:	65
Lever Length:	140
Bar:	19 Dia.

BSSSSS

		 BS EN 1906		 FD30/A0	 FD120/240
---	---	---	---	--	---



SWL1191

SPIRA
Lever on Round Rose
Concealed Fix 2 Part Screw-on-Rose

Dimensions (mm):

Rose:	52 Dia.
Rose Thickness:	66
Lever Length:	133
Bar:	19 Dia.

BSSSSS

Steelworx levers are supplied with bolt through fixings and should be used in conjunction with BTL's on P437 and Eurospec locks. For matching escutcheons SWL102/103 see P87. For matching bathroom turns SWT1016/1016i and SWT1025i see P87.