

legg-A1001

## Objective

Light designed to direct a narrow intense beam of light at different distances in small area. Illuminating them properly by establishing the focal ratios best suited to each situation. Usually used in Living, Hallway, Bathroom and Etc.
Completely dustproof.
Protected against high pressure water jets.

## Obbiettivo

Luce progettata per dirigere uno stretto intenso fascio di luce a diverse distanze in piccola area. Illuminandoli correttamente stabilendo i rapporti focali migliori adatto a ogni situazione. Solitamente usato in soggiorno, corridoio, bagno ed ecc.
Completamente antipolvere.
Protetto contro i getti d'acqua ad alta pressione.




## Description

**Housing** - Die cast aluminium powder coated with choice of RAL colors.
**Diffuser** - Clear tempered glass diffuser.
**Reflector** - LED lamp reflector.


**Standards** - Manufactured in accordance with IEC 60598.
**LED** - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).


| CODE | POWER | IP | BEAM ANGLE | LUMENS | DIMENSION |
|---|---|---|---|---|---|
| legg-A1001 | 6W, 8W, 10W | 65 | 18°/24°/38° | 110 lm/W | 86 x 99mm Φ70mm |




Color Options

W S




2700K
3000K
4000K
5000K

CRI >90 | -20° C 55° C | 85~265V 50/60Hz | Drivers Leggero PHILIPS | LED Chips BRIDGELUX CREE | A++