

legg-JD8575LR

Objective

Light designed to direct a narrow intense beam of light at different distances in small area. Illuminating them properly by establishing the focal ratios best suited to each situation. Usually used in Living, Hallway, Bathroom and Etc.
Completely dustproof.
Protected against splash of water.

Obbiettivo

Luce progettata per dirigere uno stretto intenso fascio di luce a diverse distanze in piccola area. Illuminandoli correttamente stabilendo i rapporti focali migliori adatto a ogni situazione. Solitamente usato in soggiorno, corridoio, bagno ed ecc.
Completamente antipolvere.
Protetto contro gli spruzzi d'acqua.




Description

Housing - Die cast aluminium powder coated with choice of RAL colors.
Diffuser - Frosted glass diffuser.
Reflector -Pure anodized aluminium reflector.


Standards - Manufactured in accordance with IEC 60598.
LED - Reducing energy consumption, 50,000 Hrs Life span under temp(-20°C To 50°C).


CODE	POWER	IP	BEAM ANGLE	LUMENS	DIMENSION
legg-JD10080	10W	54	15°/24°/40°	110 lm/W	100 x 110mm Φ85mm



Color Options

W B





2700K
3000K
4000K
5000K

CRI >90 | -20° C 55° C | 85~265V 50/60Hz | Drivers Leggero PHILIPS | LED Chips BRIDGELUX CREE | A++