

METRIC CHART	U-STUCCO™ RDX	U-STUCCO™ XPX	U-STUCCO™ PVX
TEXTURE	SAND FINISH	SMOOTH FINISH	SAND FINISH
BAG WEIGHT	20 KG	20 KG	25 KG
BAG DIMENSIONS	78 X 58 X 20 CM	78 X 58 X 20 CM	78 X 58 X 20 CM
DRY DENSITY	350 KG/M ³	400 KG/M ³	450 KG/M ³
FIRE CLASS	A1 FIRE-RESISTANT NON-COMBUSTIBLE	A1 FIRE-RESISTANT NON-COMBUSTIBLE	A1 FIRE-RESISTANT NON-COMBUSTIBLE
ADHESIVE TENSILE STRENGTH	≥ 0,23 N/MM ²	≥ 0,30 N/MM ²	≥ 0,45 N/MM ²
THERMAL CONDUCTIVITY	T1 - 0,07 W/MK	T1 - 0,08 W/MK	T1 - 0,09 W/MK
CAPILLARY WATER ABSORPTION	90 G/ M ² / 24 HR	50 G/ M ² / 24 HR	50 G/ M ² / 24 HR
PRESSURE RESISTANCE	CS II ≥ 1,5 N/MM ²	CS II ≥ 2,0 N/MM ²	CS II ≥ 2,5 N/MM ²
COVERAGE	13.33 M ² @5MM THICK	11.40 M ² @5MM THICK	12.50 M ² @5MM THICK
SHELF LIFE	12 MONTHS	12 MONTHS	12 MONTHS