




TECHNICAL DATA SHEET

IDENTIFICATION

The Gypsemna's FIREWALL gypsum plasterboard 15.0 mm – **FW TE 15.0** - is a factory produced 1.20 m wide gypsum board offering its high quality properties of non-combustibility, fire resistance and mechanical stability that makes it suitable for screw-fastening to drywall structures in steel as well as in wooden sections. It is encased in a heavy natural-finish pink coloured paper on the face side and on strong pink coloured paper on the back side.

The face paper is folded around the tapered long edges (on the face side only) to reinforce and protect the core and cross ends are square cut. The taper allows for concealing of joints by an appropriate joint treatment.



STANDARDS

FW TE 15.0 complies with EN 520 Type F, ASTM C 1396/C 1396M - Type X and BS1230 Part 1 Type 5

SPECIFICATIONS

DIMENSIONS:

- LENGTH 2.4 M / 3 M (other lengths at request)
- WIDTH 1.2 M
- THICKNESS 15.0 mm

EDGE

Tapered (Other edges are also available)

WEIGHT

12.6 KG/M²

MINIMUM CORE DENSITY

810 KG/M³

FLEXURAL BREAKING LOAD*

- LONGITUDINAL (N) >840 (Average of face up and face down)
- TRAVERSE (N) >280 (Average of face up and face down)

NAIL PULL RESISTANCE (N)*

>500 (As per Method B)

***Tested As per ASTM C 473 – 03A / Clause 11, 12 & 13**

FIRE SAFETY:

Surface burning in accordance with **ASTM E84** gives flame spread < 25, no smoke.

HEALTH AND SAFETY:

There is no significant health hazard when using and fixing Gypsemna Firewall gypsum plasterboard. It is free from Asbestos & Strontium Sulphide.

PROPERTIES AND USAGE:

The gypsum core offers no support for combustion and temperature is kept under control until entirely calcinated. Firewall gypsum plasterboard is the ideal product for prolonged measurable fire-resistance of drywall systems. The addition of glass fibres and the special additives in the Gypsemna Firewall Board improves the cohesive properties and fire integrity properties providing greater fire resistance, as there is no volume loss. It also gives better acoustic resistance (due to the increase in the mass of the board), in comparison with the regular boards.

Part of Gypsemna drywall system: System performance warranty only by using all listed Gypsemna system components!

Gypsemna Co. (L.L.C.), Al Saraya Avenue Bldg., Al Garhoud, P.O. Box: 14424, Dubai, U.A.E T +971 4 294 7959 F +971 4 294 7604 | info@gypsemna.com | www.gypsemna.com

JAMAL AL GHURAIR GROUP

Doc/Tds/FW TE 15.0/16/Rev:1