# XNO-L6080R

2M H.265 NW IR Bullet Camera



## Key Features

- Max. 2megapixel (1920 x 1080) resolution
- 3.2 ~ 10mm (3.1x) motorized varifocal lens
- Max. 60fps@all resolutions (H.265 / H.264)
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Day & Night (ICR), WDR (120dB), Defog
- Tampering, Defocus detection
- Motion Detection, Handover
- SD/SDHC/SDXC memory slot (Max. 256GB)
- Hallway view, WiseStreamII support
- IR viewable length 30m
- IP66, IK10, PoE support

## Accessories (Optional)



SBO-126B



SBP-302PM

12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

Hanwha Techwin


| | |
|---|---|
| **Video** | |
| Imaging Device | 1/2.8" 2MP CMOS |
| Effective Pixels | 1945(H)x1109(V) |
| Min. Illumination | Color: 0.03Lux(F1.6, 1/30sec)<br>BW: 0Lux(IR LED on) |
| Video Out | CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation<br>USB: Micro USB Type B, 1280x720 for installation |
| **Lens** | |
| Focal Length (Zoom Ratio) | 3.2~10mm(3.1x) motorized varifocal |
| Max. Aperture Ratio | F1.6(Wide) ~ F2.9(Tele) |
| Angular Field of View | H: 109.0°(Wide)~33.2°(Tele) / V: 57.4°(Wide)~18.7°(Tele) / D: 132.0°(Wide)~38.0°(Tele) |
| Min. Object Distance | 0.5m(1.64ft) |
| Focus Control | Simple focus |
| Lens Type | DC auto iris |
| **Operational** | |
| IR Viewable Length | 30m(98.42ft) |
| Camera Title | Displayed up to 85 characters |
| Day & Night | Auto(ICR) |
| Backlight Compensation | BLC, HLC, WDR, SSDR |
| Wide Dynamic Range | 120dB |
| Digital Noise Reduction | SSNR V |
| Digital Image Stabilization | Support |
| Defog | Support |
| Motion Detection | 8ea, 8point polygonal zones |
| Privacy Masking | 32ea, polygonal zones<br>- Color: Grey/Green/Red/Blue/Black/White<br>- Mosaic |
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| LDC | Support |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (2~1/12,000sec) |
| Video Rotation | Flip, Mirror, Hallway view(90˚/270˚) |
| Analytics | Defocus detection, Motion detection, Tampering |
| Alarm Triggers | Analytics, Network disconnect |
| Alarm Events | File upload via FTP and e-mail<br>Notification via e-mail<br>SD/SDHC/SDXC or NAS recording at event triggers<br>Handover |
| **Network** | |
| Ethernet | RJ-45(10/100BASE-T) |
| Video Compression | H.265/H.264: Main/Baseline/High, MJPEG |
| Resolution | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |

 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

| | |
|---|---|
| Max. Framerate | H.265/H.264: Max. 60fps/50fps(60Hz/50Hz)<br>MJPEG: Max. 30fps/25fps(60Hz/50Hz) |
| Smart Codec | Manual(5ea area), WiseStream Ⅱ |
| Bitrate Control | H.264/H.265: CBR or VBR<br>MJPEG: VBR |
| Streaming | Unicast(20 users) / Multicast<br>Multiple streaming(Up to 5 profiles) |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour |
| Security | HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access Log<br>802.1X Authentication(EAP-TLS, EAP-LEAP) |
| Edge Storage | Micro SD/SDHC/SDXC 1slot 256GB |
| Application Programming Interface | ONVIF Profile S/G<br>SUNAPI(HTTP API)<br>Wisenet open platform |
| Web Viewer | Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12<br>Recommended Browser: Google Chrome<br>Supported Browser: MS Explore11, MS Edge, Mozilla Firefox(Window 64bit only), Apple Safari(Mac OS X only) |
| Memory | 1024MB RAM, 512MB Flash |
| **Environmental** | |
| Operating Temperature / Humidity | -40°C ~ +55°C(-40°F ~ +131°F) / Less than 90% RH |
| Storage Temperature / Humidity | -50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH |
| Certification | IP66, IK10 |
| **Electrical** | |
| Input Voltage | PoE(IEEE802.3af, Class3) |
| Power Consumption | PoE: Max. 11W, typical 5W |
| **Mechanical** | |
| Color / Material | Dark grey / Aluminum |
| Product dimensions / weight | Ø91x322.9mm(Ø3.58x127.1"), 1,298g(4.25 lb) |

- The lastest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin , formerly known as Samsung Techwin.

12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.




XNO-L6080R
UNIT : mm[inch]

FC UL CE EAC 12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

Hanwha Techwin