# XND-6081RF

2M H.265 NW IR Dome Camera



## Key Features

- Max. 2Megapixel resolution
- 0.015Lux@F1.4 (Color), 0Lux (B/W, IR LED on)
- Day & Night (ICR), WDR (150dB / 120dB)
- Modular structure
- Hallway View, WiseStreamII Support
- Video & audio analytics, Audio playback
- DIS and shock detection with built-in gyro sensor
- IP52, IK10, PoE, 12VDC

12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

| | |
|---|---|
| **Video** | |
| Imaging Device | 1/2.8" 2MP CMOS |
| Effective Pixels | 1945(H)x1097(V) |
| Min. Illumination | Color: 0.015Lux(F1.4, 1/30sec)<br>BW: 0Lux(IR LED) |
| Video Out | CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation<br>USB: Micro USB Type B, 1280x720 for installation |
| **Lens** | |
| Focal Length (Zoom Ratio) | 2.8~12mm(4.3x) motorized varifocal |
| Max. Aperture Ratio | F1.4(Wide)~F3.6(Tele) |
| Min. Object Distance | 0.5m(1.64ft) |
| Focus Control | Simple focus |
| Lens Type | DC auto iris, P iris |
| **Pan / Tilt / Rotate** | |
| Pan / Tilt / Rotate Range | 0˚~360˚ / -45˚~85˚ / 0˚~355˚ |
| **Operational** | |
| IR Viewable Length | 50m(164.04ft) |
| Camera Title | Displayed up to 85 characters |
| Day & Night | Auto(ICR) |
| Backlight Compensation | BLC, HLC, WDR, SSDR |
| Wide Dynamic Range | 150dB |
| Digital Noise Reduction | SSNR V |
| Digital Image Stabilization | Support(built-in gyro sensor) |
| Defog | Support |
| Motion Detection | 8ea, 8point polygonal zones |
| Privacy Masking | 32ea, polygonal zones<br>- Color: Grey/Green/Red/Blue/Black/White<br>- Mosaic |
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| LDC | Support |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (2~1/12,000sec) |
| Video Rotation | Flip, Mirror, Hallway view(90˚/270˚) |
| Analytics | Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Digital auto tracking, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, Shock detection |
| Business Intelligence | People counting, Queue management, Heatmap |
| Alarm I/O | Input 1ea / Output 1ea |
| Alarm Triggers | Analytics, Network disconnect, Alarm input |
| Alarm Events | File upload via FTP and e-mail<br>Notification via e-mail<br>SD/SDHC/SDXC or NAS recording at event triggers<br>Alarm output<br>Handover<br>Audio playback |

 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

| | |
|---|---|
| Audio In | Selectable(mic in/line in)<br>Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm |
| Audio Out | Line out, Max. output level: 1Vrms |
| **Network** | |
| Ethernet | RJ-45(10/100BASE-T) |
| Video Compression | H.265/H.264: Main/Baseline/High, MJPEG |
| Resolution | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate | H.265/H.264: Max. 60fps/50fps(60Hz/50Hz)<br>MJPEG: Max. 30fps/25fps(60Hz/50Hz) |
| Smart Codec | Manual(5ea area), WiseStream Ⅱ |
| Bitrate Control | H.264/H.265: CBR or VBR<br>MJPEG: VBR |
| Streaming | Unicast(20 users) / Multicast<br>Multiple streaming(Up to 10 profiles) |
| Audio Compression | G.711 u-law /G.726 Selectable<br>G.726(ADPCM) 8KHz, G.711 8KHz<br>G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps<br>AAC-LC: 48Kbps at 16KHz |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP |
| Security | HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access Log<br>802.1X Authentication(EAP-TLS, EAP-LEAP) |
| Edge Storage | Micro SD/SDHC/SDXC 2slot 512GB |
| Application Programming Interface | ONVIF Profile S/G/T<br>SUNAPI(HTTP API)<br>Wisenet open platform |
| Web Viewer | Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12<br>Recommended Browser: Google Chrome<br>Supported Browser: MS Explore11, MS Edge, Mozilla Firefox(Window 64bit only), Apple Safari(Mac OS X only) |
| Memory | 1024MB RAM, 256MB Flash |
| **Environmental** | |
| Operating Temperature / Humidity | -25°C~+60°C (-13°F~+140°F) / Less than 90% RH |
| Storage Temperature / Humidity | -50°C~+60°C (-58°F~+140°F) / Less than 90% RH |
| Certification | IP52, IK10 |
| **Electrical** | |
| Input Voltage | PoE(IEEE802.3af, Class3), 12VDC |
| Power Consumption | PoE: Max 12.95W, typical 9.40W<br>12VDC: Max 10.8W, typical 7.60W |
| **Mechanical** | |
| Color / Material | White / Aluminum(Plenum) |
| RAL Code | RAL9003 |
| Product dimensions / weight | Ø205x155mm(8.07x6.10"), 1.80kg(3.97 lb) |

FC | cULus LISTED | CE | EAC 12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.


- The lastest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin , formerly known as Samsung Techwin.


12-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.


# APPERANCE-XND-6081FZ/8081FZ/6081F/6081RF/8081RF


Unit : mm (inch)
SCALE : 1
ver.19 03

## X-PLUS FLUSH DOME







Hanwha Techwin
FC CE EAC 12-2019 © 2020 Hanwha Techwin Co., Ltd. All rights reserved.