PNM-9081VQ

20M H.265 Multi-directional Camera



Key Features

- 4ea x 2560 x 1920 resolution (Max. 20MP)
- 4ea x 3.6 ~ 9.4mm (2.6x) motorized varifocal lens
- 4ea x Max. 30fps@5M (H.265, H.264)
- Digital Image Stabilization with Built-in Gyro Sensor
- H.265, H.264, MJPEG Codec Supported
- Day & Night (ICR), WDR (120dB)
- Motion detection, Tampering
- Advanced Video Analytics
- SD / SDHC / SDXC Memory slot, WiseStreamII Support

Accessories (Optional)


SBP-329HM


SBP-317HM


SBP-390WM2


SBP-300WM1


SBP-300WM


SBP-300NB


SBP-300KM


SBP-300CM


SBP-300LM


SBP-300PM


SBP-300B

08-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

Hanwha Techwin

Video	
Imaging Device	1/1.8" 6MP CMOS: each CH
Effective Pixels	3096(H)x2094(V): each CH
Min. Illumination	Color: 0.07Lux(F1.2, 1/30sec)(30IRE) B/W: 0.007Lux (F1.2, 1/30sec)(30IRE)
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation
Lens	
Focal Length (Zoom Ratio)	3.6~9.4mm(2.6x) motorized varifocal
Max. Aperture Ratio	F1.2(Wide)~F2.4(Tele)
Angular Field of View	H: 102.5˚(Wide)~38.7˚(Tele), V: 74.2˚(Wide)~29.0˚(Tele), D: 135.5˚(Wide)~48.6˚(Tele)
Min. Object Distance	0.5m(1.64ft)
Focus Control	Simple focus
Lens Type	DC auto iris, P iris
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	Quad mode: Pan +/-30˚, Tilt 10˚ ~ 41˚, Rotate +-90˚ Center mode: Pan +/-60˚, Tilt 10˚ ~ 41˚ / 10˚ ~ 90˚(CH2/Center), Rotate +-90˚
Operational	
Camera Title	Displayed up to 85 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V
Digital Image Stabilization	Support(built-in gyro sensor)
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, polygonal zones - Color: Grey/Green/Red/Blue/Black/White - Mosaic
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/12,000sec)
Video Rotation	Flip, Mirror, Hallway view(90˚/270˚)
Analytics	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Analytics, Network disconnect, Alarm input
Alarm Events	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC recording at event triggers Alarm output
Network	
Ethernet	RJ-45(10/100/1000BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG


 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

Resolution	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 720x576, 720x480, 640x480, 320x240
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
Smart Codec	Manual(5ea area), WiseStream Ⅱ
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 10 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP)
Edge Storage	Micro SD/SDHC/SDXC 4slot 256GB(Each CH)
Application Programming Interface	ONVIF Profile S SUNAPI(HTTP API)
Web Viewer	Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12 Recommended Browser: Google Chrome Supported Browser: MS Explore11, MS Edge, Mozilla Firefox(Window 64bit only), Apple Safari(Mac OS X only)
Memory	5GB RAM, 1280MB Flash
Environmental	
Operating Temperature / Humidity	-40°C ~ +55°C(-40°F ~ +131°F) / Less than 90% RH
Storage Temperature / Humidity	-50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH
Certification	IP66, IK10
Electrical	
Input Voltage	HPoE(IEEE802.3bt), 12VDC
Power Consumption	HPoE: Max 33.6W 12VDC: Max 28.8W
Mechanical	
Color / Material	Ivory / Aluminum
Product dimensions / weight	Ø314mmx152mm, 4890g

- The lastest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin , formerly known as Samsung Techwin.

08-2019 ©2020 Hanwha Techwin Co., Ltd. All rights reserved.

Hanwha Techwin



 © 2020 Hanwha Techwin Co., Ltd. All rights reserved.