SEWAGE PUMP - BLUE



DESCRIPTION

This Submersible Pump With Is Configured To Use With Dirty Water Which Is Not Chemically Aggressive Towards The Materials From Which The Pumps Are Made.

KEY FEATURES

- Fast and effective reliability
- And easy to use long-lasting
- Protection from overload

APPLICATIONS

- Clearing dirty water
- Discharging domestic waste water
- Emptying collection traps containing
- Partical upto a maximum of φ35mm

OPERATING CONDITIONS

- 5m maximum immersion depth liquid
- Temperature upto 35°c maximum
- Ambient temperature 40°c

SEWAGE PUMP - BLUE

MODEL : WQ15-45-4

POWER	Q(m3/h)	0	6	12	18	24	3	36
KWHP	Q(1/min	0	100	200	300	40	0	60
2.23		2	18.5	17.5	16.5			
		0						

MODEL : WQ15-55-5.5

Power	Q(m3/h)	0	6	12	18	24	3	36
KWHP	Q(1/min	0	100	200	30	40	0	60
45.5		3	33	31.5				
	H	5			30			

MODEL : WQ30-26-4

Power	Q(m3/h)	0	6	12	18	24	30	36
KWHP	Q(1/min	0	100	200	30	400	50	60
5.57.5		3	36	35.5		33.5	31.8	
	H	8			35			29



SEWAGE PUMP - BLUE



MOTOR-SPECIFICATION

Two- Pole Induction	n=2850 r.p.m
Motor Insulation Class	B
Protection	IP68
Continuous Service	SI
Shield	Thermal Protector

COMPONENT CONSTRUCTION

Two- Pole Induction	n=2850 r.p.m
Motor Insulation Class	B
Protection	IP68
Continuous Service	SI
Shield	Thermal Protector