CLEAN WATER PUMP



DESCRIPTION

Description: This model of pump is characterized with high heads, compact size, light weight and convenient use and vastly used in high position water delivery, flush and places as construction sites. The float switch can automatically control on and off with the change of the water level. The protector in the motor can automatically cut off the power when it is overheated

CLEAN WATER PUMP

APPLICATIONS

- House hold water supply
- Garden watering Pressure
- Boosting system Agriculture
- Irrigation

SPECIFICATION

Two- Pole Induction	Single Phase 220V ± 10%, 50 Hz
Motor Water Temperature	Up to 45o C
Power	0.75 to 2.2 Kw
Insulation Class	F
Protection Class	IP 68
Capacity	Up to 15 cu.m/h
Head	Up to 72m
Max. Immersion Depth	5m
PH	6.5 to 8.5
Grain Diameter	Not Bigger than 0.2 mm

CLEAN WATER PUMP

MODEL: CUT-1500

Power		Voltage	Outlet Max. Max.			Flow Head Q M3/H 0		4	9	13	18 4	22 5	26	31	35	40	44
								1	2	3	67	83	6	7	8	9	10
KW	HP		(Inch)	(IPM)	(m)	LPM 0		17	33	50	25.5	23.5	100	117	133	150	167
1.1	1.5	220V	2	250	30		H Meters	30	29	28	27			20.5	17	14	10	6

MODEL: WQD 1500 –B

Power		Voltage	Outlet Max. Max. Flow Head			Q	USGPM 0		4	9	13	18	22	26	31	35	40	44
							M3/H 0		1	2	3	4	5	6	7	8	9	10
KW	HP		(Inch)	(IPM)	(m)		LPM 0		17	33	50	67	83	100	117	133	150	167
1.1	2	220V	2	250	42	H Meters		42	40	38	36	34	31	27.5	22	16	9	4

MODEL: WQD 1100 –B

Power		Voltage	Outlet Max. Max.			Flow Head Q M3/H 0		4	9	13	18	22 5	26	31	35	40	44
								1	2	3	4	83	6	7	8	9	10
KW	HP		(Inch)	(IPM)	(m)	LPM 0		17	33	50	67	32.5	100	117	133	150	167
2.2	3	220V	2H Meters				175 72 72	67	61	54	45		20.5	8			

HYDRAULIC PERFORMANCE CURVE

