CLEAN WATER PUMP – STAINLESS STEEL



DESCRIPTION

The submersible pump with stainless steel is configured to use with clean water that does not contain any abrasive particles.

KEY FEATURES

- Fast and Effective
- Reliability and Easy to Use Long-Lasting
- Protection from Overload

CLEAN WATER PUMP – STAINLESS STEEL

APPLICATIONS

- Domestic
- Gardening
- Irrigation
- Emptying Tanks

OPERATING CONDITIONS

- 3 m Maximum Immersion Depth Liquid
- Temperature up to 35°C Maximum
- Ambient Temperature 40°C

MODEL: QDS-370D

Power(IN)	Q (m3h)	0	0.9	1.8	2.7	3.6	4.5	5.4	6.3	7.2	8.1
KW HP	Q (l/min)	0	15	30	45	60	75	90	105	120	135
0.37 0.5	H	7	6.5	6	5.5	5	4.5	3.8	2.8	1.5	

MODEL: QDS-550D

Power(IN)	Q (m3h)	0	0.9	1.8	2.7	3.6	4.5	5.4	6.3	7.2	8.1
KW HP	Q (l/min)	0	15	30	45	60	75	90	105	120	135
0.55 0.75	H	9	8	7.5	7	6.5	6	5.5	5	4	3

MODEL: QDS-550D

Power(IN)	Q (m3h)	0	0.9	1.8	2.7	3.6	4.5	5.4	6.3	7.2	8.1
KW HP	Q (l/min)	0	15	30	45	60	75	90	105	120	135
0.75 1	H	10	9	8.5	8	7.5	7	6.5	5.6	4.8	4

CLEAN WATER PUMP – STAINLESS STEEL

MOTO - SPECIFICATION

Two—pole induction motor	n=2850 r.p.m
Insulation Class	B
Protection	IP68
Continuous service	S1
Shield	Thermal protector

COMPONENT CONSTRUCTION

Pump body	AISI304 SS
Suction filter	Techno polymer
Impeller	Noryl
Motor shaft	AISI304 SS
Mechanical seal	Ceramic/Graphite
Cable	6m power cable with plug