Sheet1

Company	Model	Performance Characteristics
	Fire resisting steel rolling shutte	Fire Rated Steel rolling shutter with clear opening. Fire rating: up to 240min § Fire rating: up to 240min § Fire rating: up to 240min Maximum dimension: 7m high x 7m wide§ Maximum dimension: 7m high x 7m wide§ Maximum dimension: 7m high x 7m wide
	FD120 & FD240 steel hinged do	Fire Rated Steel Hinged Doorsets. ■ Double Leaf: 2090mm high x 1740 wide → 240 mins § Double Leaf: 2090mm high x 1740 wide → 240 mins § Double Leaf: 2090mm high x 1740 wide → 240 mins ■ Double Leaf 2090mm high x 1740 wide → 120 mins§ Double Leaf 2090mm high x 1740 wide → 120 mins§ Double Leaf 2090mm high x 1740 wide → 120 mins
		 Double Leaf 2200mm high x 1400 wide → 240 mins§ Double Leaf 2200mm high x 1400 wide → 240 mins§ Double Leaf 2200mm high x 1400 wide → 240 mins Double Leaf 2093mm high x 1997 wide → 240 mins§ Double Leaf 2093mm high x 1997 wide → 240 mins§ Double Leaf 2093mm high x 1997 wide → 240 mins§
	Fire rated steel door 180 mins	 Fire Rated Swinging Door and Frame assemblies. Fire rating: up to 180min § Fire rating: up to 180min § Fire rating: up to 180min Door Size: 2438mm wide x 3048mm high§ Door Size: 2438mm wide x 3048mm high§ Door Size: 2438mm wide x 3048mm high Door Frame: 2550mm wide x 3112mm high§ Door Frame: 2550mm wide x 3112mm high§
	BST T90-1 & BST T90-2	 Fire Rated Swinging Door and Frame assemblies. Fire rating: up to 90min § Fire rating: up to 90min § Fire rating: up to 90min Maximum sizes: 2510mm wide x 2505mm high x 64mm thick§ Maximum sizes: 2510mm wide x 2505mm high x 64mm thick§ Maximum sizes: 2510mm wide x 2505mm high x 64mm thick
Moment	OST-2.1 & OST-2.2	Fire Rated Swinging Door and Frame assemblies. • Fire rating: up to 180min § Fire rating: up to 180min

Sheet1

Fireguard LLC	■ Maximum sizes: 2510mm wide x 2505mm high x 116mm thick§ Maximum sizes: 2510mm wide x 2505mm high x 116mm thick
	Fire Rated Swinging Door and Frame assemblies.
SYSTEM SOMMER - S1	■ Fire rating: up to 180min § Fire rating: up to 180min
	 Maximum sizes: 2700mm wide x 2600mm high x 64mm thick§ Maximum sizes: 2700mm wide x 2600mm high x 64mm thick
	Special purpose type fire gate with steel sheets and steel frame.
	• Fire rating: up to 90min § Fire rating: up to 90min
Fire rated steel door E90	Single Leaf with a clear opening size of the frame: 1,160mm wide x 2,205mm high x 64mm thick§ Single Leaf with a clear opening size of the frame: 1,160mm wide x 2,205mm high x 64mm thick
	■ Double Leaf with a clear opening size of the frame: 2,900mm wide x 2,955mm high x 64mm thick§ Double Leaf with a clear opening size of the frame: 2,900mm wide x 2,955mm high x 64mm thick
	Special purpose type fire gate with steel sheets and steel frame.
	■ Fire rating: up to 120min § Fire rating: up to 120min
	 Single Leaf with a clear opening size of the frame: 1,160mm wide x 2,205mm high x 88mm thick§ Single Leaf with a clear opening size of the frame: 1,160mm wide x 2,205mm high x 88mm thick
Fire rated steel door E120	■ Double Leaf with a clear opening size of the frame: 2,400mm wide x 2,660mm high x 98mm thick§ Double Leaf with a clear opening size of the frame: 2,400mm wide x 2,660mm high x 98mm thick
	Double Leaf with a clear opening size of the frame: 2,410mm wide x 2,205mm high x 89mm thick§ Double Leaf with a clear opening size of the frame: 2,410mm wide x 2,205mm high x 89mm thick
	Special purpose type fire gate with steel sheets and steel frame.
Fire rated steel door E120	■ Fire rating: up to 120min
	 Double Leaf with a clear opening size of the frame: 3,500mm wide x 3,590mm high x 111mm thick