

Oculo LED Square Trio

Oculo LED V2 Square Trio Warm White - High Output

3032447



Product features

- Integrated LED adjustable gimbal downlight, triple head, high output, ideal for retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 28°, optics: interchangeable aluminium reflector, colour temperature: 3000K warm white, total system power: 144W, total fixture output: 3 x 4191lm, 87lm/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, lifetime: 50,000 hours at 70% of the original output (L70B50), energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 45°, reflector accessories available, ceiling cut-out: 455x177mm, dimensions: 500x200x129mm, weight: 3.90kg.



PRODUCT OVERVIEW

IPC Code	3032447
Product name	Oculo LED V2 Square Trio Warm White - High Output
Technology	LED
Housing	Die cast Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Retail
Certifications	EUNEW008
E-number FI	4271382
Fixture luminous flux (lm)	4191 x 3
Luminaire efficacy (lm/W)	87
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	90
Colour Consistency (SDCM)	3
Beam Angle (°)	28
Photobiological Risk Group	Group 1
Total power consumption (W)	144
Electrical protection	Class II
Control gear type	Electronic
Average life (Nominal) (h)	50000
Housing colour	White - RAL9010
IP rating	IP20
IK rating	IK02
Product EAN number	8711971324478
Included lamp	INTEGRATED LED

DATA TABLE

General data

Oculo LED Square Trio

Oculo LED V2 Square Trio Warm White - High Output

3032447

IPC Code	3032447
Product name	Oculo LED V2 Square Trio Warm White - High Output
Technology	LED
Housing	Die cast Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Retail
Certifications	EUNEW008
E-number FI	4271382

Optical data

Fixture luminous flux (lm)	4191 x 3
Luminaire efficacy (lm/W)	87
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	90
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	28
Distribution type	Direct
Photobiological Risk Group	Group 1

Electrical data

Total power consumption (W)	144
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class II
Control gear type	Electronic
Drive current (mA)	1200
Inrush Current (A)	20
Inrush Duration (µs)	200
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	28

Lifetime data

Average life (Nominal) (h)	50000
----------------------------	-------

Physical data

Vertical Tilt (°)	45
Horizontal rotation (°)	355
Housing colour	White - RAL9010
IP rating	IP20
IK rating	IK02
Reflector finish	Aluminium Reflector
Nominal Product Length (mm)	500
Nominal Product Width (mm)	200
Weight (kg)	3.72
Recessed Depth (mm)	129

Oculo LED Square Trio


Oculo LED V2 Square Trio Warm White - High Output

3032447

Packaging

Single packaging type	Carton
Product EAN number	8711971324478
Packaging single length / height (cm)	50.0
Packaging single width (cm)	30.0
Packaging single depth (cm)	20.0
DUN14 (outer)	08711971324478
Units per outer package	1
Packaging outer length / height (cm)	50.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	20.0


TECHNICAL DRAWINGS




Oculo LED Square Trio


Oculo LED V2 Square Trio Warm White - High Output
3032447


Lumiance 3032447


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

Lumiance 3032447  874/2012