Myriad V Residential LED - Housing only

MYRDHS ST 4K PHDM WHT

2057989



Product features

- The Myriad Housing 4000K Spot accent downlight is a high efficient 10W recessed spotlight, luminous flux: 1170lm, luminaire efficacy 117lm/W. Colour rendering index Ra>80, Colour temperature 4000K, Beam angle 28ø, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions: 76mm.

PRODUCT OVERVIEW

IPC Code	2057989
Product name	MYRDHS ST 4K PHDM WHT
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1170
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	85
Beam Angle (°)	28
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Average life (Nominal) (h)	50000
Housing colour	White Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768579891
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2057989
Product name	MYRDHS ST 4K PHDM WHT
Technology	LED
Housing	Aluminium

© Feilo Sylvania | Date Printed: 17 Nov 2018

Myriad V Residential LED - Housing only

MYRDHS ST 4K PHDM WHT

2057989

Mount	Ceiling recessed
Environment	Integral
General application	Museums & Galleries,Office,Retail,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	1170
Luminaire efficacy (lm/W)	117
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	28
Distribution type	Direct

Electrical data

Total power consumption (W)	10
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	10
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	50000

Physical data

Housing colour	White Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	White Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	0.39
Recessed Depth (mm)	72

Packaging

Single packaging type	Carton
Product EAN number	5025768579891
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
DUN14 (outer)	05025768579891
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0

© Feilo Sylvania | Date Printed: 17 Nov 2018


Myriad V Residential LED - Housing only


MYRDHS ST 4K PHDM WHT

2057989


Packaging outer depth (cm)	17.5

PHOTOMETRY





TECHNICAL DRAWINGS





© Feilo Sylvania | Date Printed: 17 Nov 2018

Myriad V Residential LED - Housing only

MYRDHS ST 4K PHDM WHT

2057989





© Feilo Sylvania | Date Printed: 17 Nov 2018