

#### **Product features**

The Myriad Housing 2700K Spot accent downlight is a high efficient 12W recessed spotlight, luminous flux: 1286lm, luminaire efficacy 107lm/W. Colour rendering index Ra>80, Colour temperature 2700K, Beam angle 28ø, Average life rated at 50,000Hrs L70B50, Protection rating IP20, Cut out dimensions:











### PRODUCT OVERVIEW

IPC Code	2058008
Product name	MYRDHS ST 2.7K DALIEM BLK
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Hospitality,Office,Retail,Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	1286
Luminaire efficacy (lm/W)	107
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Beam Angle (°)	28
Luminous flux (emergency) (lm)	275
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	1
Average life (Nominal) (h)	50000
Housing colour	Black Trim
IP rating	IP20
IK rating	IK02
Product EAN number	5025768580088
Lamps	Yes
Included lamp	INTEGRATED LED

### **DATA TABLE**

General c	lata
-----------	------

IPC Code	2058008
Product name	MYRDHS ST 2.7K DALIEM BLK




Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Integral
General application	Hospitality,Office,Retail,Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUNEW008
ETIM Class	EC001744
Optical data	
Fixture luminous flux (lm)	1286
Luminaire efficacy (lm/W)	107
LOR (%)	100
Colour temperature (K)	2700
CRI (Ra)	85
Adjustable chromaticity	N
Beam Angle (°)	28
Distribution type	Direct
Luminous flux (emergency) (lm)	275
Emergency duration (h)	3
Electrical data	
Total power consumption (W)	12
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	1
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	50000
Physical data	
Housing colour	Black Trim
IP rating	IP20
IK rating	IK02
Diffuser finish	Black Trim
Reflector finish	Aluminium
Nominal Product Height (mm)	72
Weight (kg)	1.39
Recessed Depth (mm)	72
-	
Packaging	
Single packaging type	Carton
Product EAN number	5025768580088
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5



DUN14 (outer)	05025768580088
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5

### **PHOTOMETRY**



### **TECHNICAL DRAWINGS**

