

Product features

• MYRIADSS IP65 4000K ELE WH EM













PRODUCT OVERVIEW


2050672
MYRIAD SS IP65 4000K ELE WH EM
LED
Ceiling recessed
Interior
Hospitality,Office,Retail,Residential & Consumer
EUNEW001
EC001744
68
100
4000
80
30
12
Class II
Electronic + Emergency
Integral
IP65
5025768506729
INTEGRATED LED

DATA TABLE


General data	
IPC Code	2050672
Product name	MYRIAD SS IP65 4000K ELE WH EM
Technology	LED
Mount	Ceiling recessed
Environment	Interior
General application	Hospitality,Office,Retail,Residential & Consumer
Certifications	EUNEW001
ETIM Class	EC001744


Optical data	
Luminaire efficacy (lm/W)	68
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Adjustable chromaticity	N
Beam Angle (°)	30
Distribution type	Direct symmetrical
Electrical data	
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	Electronic + Emergency
Control gear mounting	Integral
Drive current (mA)	250
Nominal Frequency (Hz)	50/60Hz
Physical data	
IP rating	IP65
Diffuser material	Glass
Weight (kg)	1.37
Recessed Depth (mm)	72
Packaging	
Single packaging type	Carton
Product EAN number	5025768506729
Packaging single length / height (cm)	27.5
Packaging single width (cm)	25.0
Packaging single depth (cm)	12.5
Units per outer package	1
Packaging outer length / height (cm)	27.5
Packaging outer width (cm)	25.0


PHOTOMETRY



Packaging outer depth (cm)







TECHNICAL DRAWINGS

