Giotto LED 305

GIOTTO 305 MM LED G2 3000K SURFACE MW

3034777



Product features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1491 lm, 19W, 78lm/W, 3000K, CRI 80, non-dimmable, integral microwave sensor. 50,000 hours lumen maintenance. Drive current: 700mA, IP44, IK10, Class I, 220-240V, Energy class: A++, A+, A.

PRODUCT OVERVIEW

IPC Code	3034777
Product name	GIOTTO 305 MM LED G2 3000K SURFACE MW
Technology	LED
Housing	Polycarbonate
Environment	Internal, External
General application	Hospitality,Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
Fixture luminous flux (lm)	1539
Luminous flux (lm)	1491
Luminaire efficacy (lm/W)	78
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	23.7
Photobiological Risk Group	0 (exempt)
Total power consumption (W)	19
Electrical protection	Class I
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971347774
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	3034777
Product name	GIOTTO 305 MM LED G2 3000K SURFACE MW
Technology	LED
Housing	Polycarbonate
Environment	Internal, External

© Feilo Sylvania | Date Printed: 20 Nov 2018

Giotto LED 305

GIOTTO 305 MM LED G2 3000K SURFACE MW

3034777

General application	Hospitality,Logistics & Industry
Operating temperature range (°C)	-25°C to +25°C
Certifications	EUNEW009
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	1539
Luminous flux (lm)	1491
Luminaire efficacy (lm/W)	78
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Distribution type	Direct
Glare control	23.7
Photobiological Risk Group	0 (exempt)

Electrical data

Total power consumption (W)	19
Mains voltage (V)	220-240V~
Electrical protection	Class I
Drive current (mA)	700
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 13A C Breaker	65
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 20A C Breaker	100
Max. Luminaires per 10A B Breaker	30
Max. Luminaires per 13A B Breaker	39
Max. Luminaires per 16A B Breaker	48
Max. Luminaires per 20A B Breaker	60

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	40000
Lumen maintenance - L90 B10	32000

Physical data

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Length (mm)	305
Nominal Product Width (mm)	305

© Feilo Sylvania | Date Printed: 20 Nov 2018

Giotto LED 305

GIOTTO 305 MM LED G2 3000K SURFACE MW


3034777


Nominal Product Height (mm)	104
Weight (kg)	1.11

Packaging


Single packaging type	Carton
Product EAN number	8711971347774
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	10.0
DUN14 (outer)	08711971347774
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	10.0

PHOTOMETRY





TECHNICAL DRAWINGS




© Feilo Sylvania | Date Printed: 20 Nov 2018

Giotto LED 305

GIOTTO 305 MM LED G2 3000K SURFACE MW

3034777



© Feilo Sylvania | Date Printed: 20 Nov 2018