Giotto LED 305

GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY

3034791



Product features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1490 lm, 20W, 75lm/W, 3000K, CRI 80, DALI, integral 3 hour maintained emergency, 50,000 hours lumen maintenance. Drive current: 700mA, IP44, IK10, Class I, 220-240V, Energy class: A++, A+, A.

PRODUCT OVERVIEW

IPC Code	3034791
Product name	GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY
Technology	LED
Housing	Polycarbonate
Environment	Internal
General application	Hospitality,Logistics & Industry
Certifications	EUNEW001
ETIM Class	EC002892
Fixture luminous flux (lm)	1490
Luminous flux (lm)	1490
Luminaire efficacy (lm/W)	75
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	23.8
Photobiological Risk Group	0 (exempt)
Luminous flux (emergency) (lm)	102
Total power consumption (W)	20
Electrical protection	Class I
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971347910
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	3034791
Product name	GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY

© Feilo Sylvania | Date Printed: 20 Nov 2018

Giotto LED 305

GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY

3034791

Technology	LED
Housing	Polycarbonate
Environment	Internal
General application	Hospitality,Logistics & Industry
Operating temperature range (°C)	0°C to +25°C
Certifications	EUNEW001
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	1490
Luminous flux (lm)	1490
Luminaire efficacy (lm/W)	75
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Distribution type	Direct
Glare control	23.8
Photobiological Risk Group	0 (exempt)
Luminous flux (emergency) (lm)	102
Emergency duration (h)	3

Electrical data

Total power consumption (W)	20
Mains voltage (V)	220-240V~
Electrical protection	Class I
Drive current (mA)	700
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 13A C Breaker	65
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 20A C Breaker	100
Max. Luminaires per 10A B Breaker	30
Max. Luminaires per 13A B Breaker	39
Max. Luminaires per 16A B Breaker	48
Max. Luminaires per 20A B Breaker	60

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	40000
Lumen maintenance - L90 B10	32000

Physical data

Housing colour	White
IP rating	IP44

© Feilo Sylvania | Date Printed: 20 Nov 2018

Giotto LED 305

GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY


3034791

IK rating	IK10
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Length (mm)	305
Nominal Product Width (mm)	305
Nominal Product Height (mm)	104
Weight (kg)	1.41

Packaging

Single packaging type	Carton
Product EAN number	8711971347910
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	10.0
DUN14 (outer)	08711971347910
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	10.0

PHOTOMETRY




© Feilo Sylvania | Date Printed: 20 Nov 2018


Giotto LED 305

GIOTTO 305 MM LED G2 3000K RECESSED DALI EMERGENCY

3034791

TECHNICAL DRAWINGS





© Feilo Sylvania | Date Printed: 20 Nov 2018