

Giotto LED 335

GIOTTO 335 MM LED G2 4000K SURFACE DALI

3034804



Product features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2225 lm, 23W, 97lm/W, 4000K, CRI 80, DALI, 50,000 hours lumen maintenance. Drive current: 700mA, IP44, IK10, Class I, 220-240V, Energy class: A++, A+, A.



PRODUCT OVERVIEW

IPC Code	3034804
Product name	GIOTTO 335 MM LED G2 4000K SURFACE DALI
Technology	LED
Housing	Polycarbonate
Environment	Internal, External
General application	Hospitality, Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4270264
Fixture luminous flux (lm)	2225
Luminous flux (lm)	2225
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	25.2
Photobiological Risk Group	0 (exempt)
Total power consumption (W)	23
Electrical protection	Class I
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971348047
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	3034804
Product name	GIOTTO 335 MM LED G2 4000K SURFACE DALI
Technology	LED
Housing	Polycarbonate
Environment	Internal, External

Giotto LED 335

GIOTTO 335 MM LED G2 4000K SURFACE DALI
3034804

General application	Hospitality, Logistics & Industry
Operating temperature range (°C)	-25°C to +25°C
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4270264

Optical data

Fixture luminous flux (lm)	2225
Luminous flux (lm)	2225
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Distribution type	Direct
Glare control	25.2
Photobiological Risk Group	0 (exempt)

Electrical data

Total power consumption (W)	23
Mains voltage (V)	220-240V~
Electrical protection	Class I
Drive current (mA)	700
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 13A C Breaker	65
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 20A C Breaker	100
Max. Luminaires per 10A B Breaker	30
Max. Luminaires per 13A B Breaker	39
Max. Luminaires per 16A B Breaker	48
Max. Luminaires per 20A B Breaker	60

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	42000
Lumen maintenance - L90 B10	35000

Physical data

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Length (mm)	335

Giotto LED 335

GIOTTO 335 MM LED G2 4000K SURFACE DALI
3034804

Nominal Product Width (mm)	335
Nominal Product Height (mm)	110
Weight (kg)	1.2

Packaging


Single packaging type	Carton
Product EAN number	8711971348047
Packaging single length / height (cm)	35.7
Packaging single width (cm)	35.7
Packaging single depth (cm)	10.6
DUN14 (outer)	08711971348047
Units per outer package	1
Packaging outer length / height (cm)	35.7
Packaging outer width (cm)	35.7
Packaging outer depth (cm)	10.6

PHOTOMETRY


0.5	1.59	E(0°) E(C0)	2734 207
1.0	3.18	E(0°) E(C0)	664 52
1.5	4.76	E(0°) E(C0)	304 23
2.0	6.35	E(0°) E(C0)	171 13
2.5	7.94	E(0°) E(C0)	109 8
3.0	9.53	E(0°) E(C0)	78 6

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 115.8°)



TECHNICAL DRAWINGS



Giotto LED 335

GIOTTO 335 MM LED G2 4000K SURFACE DALI

3034804

