

## ToLEDo Superia T8 ECG

TOLEDO SUPERIA T8 ECG 2FT 1100LM865  
0027065



### Product features

- 50,000 hours average rated life (L70 F50) • Last 2.5 times longer than 600mm 18W fluorescent T8 Tri-phosphor lamp • High switching cycles - 200,000X • High lumen efficacy - 147lm/W • Omni-directional light distribution and wide beam angle • Minimum and maximum operating temperature: - 20°C to 55°C • Glass construction and polycarbonate end-caps • Not suitable for direct mains (AC 220-240V) or CCG/magnetic ballast • Works only with compatible electronic ballast. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



## PRODUCT OVERVIEW

IPC Code	0027065
Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
General application	Museums & Galleries, Residential & Consumer, Education, Logistics & Industry, Retail, Office, Hospitality,
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740534
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1100
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Wattage (W)	7.5
Product Voltage (V)	50
Average life (Nominal) (h)	50000
Product EAN number	5410288270654

## DATA TABLE

### General data

IPC Code	0027065
Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
General application	Museums & Galleries, Residential & Consumer, Education, Logistics & Industry, Retail, Office, Hospitality,
Operating temperature rated (°C)	25
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740534

## ToLEDo Superia T8 ECG

*TOLEDO SUPERIA T8 ECG 2FT 1100LM865*  
0027065

### Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1100
Luminous flux (Rated) (lm)	1100
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam angle (Rated) (°)	220
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	7.5
Watt (Rated) - High frequency (W)	7.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Product Voltage (V)	50
Lamp power factor	0.82
No. Of switching cycles before premature failures	200000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	9

### Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

### Physical data

Nominal Product Diameter (mm)	600
Weight (kg)	0.122

### Packaging

Single packaging type	Carton
Product EAN number	5410288270654
Packaging single length / height (cm)	61.0
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288270651
Units per outer package	10
Packaging outer length / height (cm)	66.5
Packaging outer width (cm)	21.3
Packaging outer depth (cm)	11.5

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes

ToLEDo Superia T8 ECG  
TOLEDO SUPERIA T8 ECG 2FT 1100LM865  
0027065

Safety message

Suitable for totally enclosed fixture

