Ascent 100 II Arch 160

ASCENT 100 II ARCH 1000 3K STD 160

2060540



Product features

- The ASCENT 100 II ARCH 1000 3K STD 160 is a high efficient non dimmable downlight luminaire, luminous flux: 968lm, luminaire efficacy: 138lm/W, Colour rendering index Ra >80, Colour temperature: 3000K Warm White, Average life rated at 50,000Hrs, Class II, Protection rating IP44/IK02, Cut out dimensions: 178mm

PRODUCT OVERVIEW

IPC Code	2060540
Product name	ASCENT 100 II ARCH 1000 3K STD 160
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
General application	Hospitality,Retail,Office,
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4260848
Fixture luminous flux (lm)	968
Luminaire efficacy (lm/W)	138
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	21.2
Photobiological Risk Group	Group 0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	Electronic
Control gear mounting	Remote
Dimmable	No
Housing colour	White - RAL9016
IP rating	IP40
IK rating	IK02
Product EAN number	5025768605408
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

© Feilo Sylvania | Date Printed: 22 Nov 2018

Ascent 100 II Arch 160

ASCENT 100 II ARCH 1000 3K STD 160

2060540

General data

IPC Code	2060540
Product name	ASCENT 100 II ARCH 1000 3K STD 160
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
General application	Hospitality,Retail,Office,
Operating temperature range (°C)	0-25
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4260848

Optical data

Fixture luminous flux (lm)	968
Luminaire efficacy (lm/W)	138
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam angle (Rated) (°)	85
Distribution type	Direct
Glare control	21.2
Photobiological Risk Group	Group 0

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear required	Yes
Control gear type	Electronic
Control gear mounting	Remote
Dimmable	No
Drive current (mA)	350
Inrush Current (A)	45
Inrush Duration (µs)	20
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 16A C Breaker	80

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Lumen maintenance - L90 B20	34000

© Feilo Sylvania | Date Printed: 22 Nov 2018

Ascent 100 II Arch 160

ASCENT 100 II ARCH 1000 3K STD 160

2060540

Lumen maintenance - L90 B10	48000


Physical data


Housing colour	White - RAL9016
IP rating	IP40
IK rating	IK02
Diffuser finish	Light Opal
Diffuser material	Arcylic
Reflector finish	Arch
Nominal Product Width (mm)	150
Nominal Product Height (mm)	94
Nominal Product Diameter (mm)	160
Weight (kg)	1.2

Packaging

Single packaging type	Carton
Product EAN number	5025768605408
Packaging single length / height (cm)	25.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	25.0
DUN14 (outer)	05025768605408
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0

PHOTOMETRY






TECHNICAL DRAWINGS


© Feilo Sylvania | Date Printed: 22 Nov 2018

Ascent 100 II Arch 160

ASCENT 100 II ARCH 1000 3K STD 160

2060540






© Feilo Sylvania | Date Printed: 22 Nov 2018

Ascent 100 II Arch 160

ASCENT 100 II ARCH 1000 3K STD 160

2060540



© Feilo Sylvania | Date Printed: 22 Nov 2018