ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830

0027106



Product features

- • A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubes. • High performance glass construction design • High lumen output - 3730lm, with an impressive lumen efficacy of 138 lm/W • Omnidirectional light distribution (320°) and wide beam angle (220°) • A++ energy rating and low power consumption • Average rated life of 50'000 hours (L70 F50) • Lamp length - 1500mm • High power factor 0.95 • 200,000 switching cycle • 5 years guarantee for complete peace of mind • Colour temperature -3000K • Suitable for outdoor applications in weather proof luminaires • Compatible with electromagnetic gear and also suitable for direct mains operation (220-240V) • No bending or discoloration over time • No contactable metal parts, therefore no potential risk of electric shock

PRODUCT OVERVIEW

IPC Code	0027106
Product name	ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830
Technology	LED
Watt (Rated) (W)	27
Lamp shape	LED Tubes T8
Cap/Base	G13
Lamp finish	Frosted
General application	Hospitality,Logistics & Industry,Residential & Consumer
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740526
E-number SE	8292490
Luminous flux (lm)	3730
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	27
Average life (Nominal) (h)	50000
Product EAN number	5410288271064
Chromaticity coordinate Y	0.403

DATA TABLE

General data

IPC Code	0027106
Product name	ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830
Technology	LED
Watt (Rated) (W)	27
Lamp shape	LED Tubes T8
Cap/Base	G13
Lamp finish	Frosted
General application	Hospitality,Logistics & Industry,Residential & Consumer

© Feilo Sylvania | Date Printed: 23 Nov 2018

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830

0027106

Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740526
E-number SE	8292490

Optical data

Luminous flux (lm)	3730
Luminous flux (Rated) (lm)	3730
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	27
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Control gear required	No
No. Of switching cycles before premature failures	200000
Transformer required	No
Drive current (mA)	120
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	27

Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

Nominal Product Length (mm)	1513
Max. Length base to base (mm) - A	1499
Length base to pin Min-Max (mm) - B	1505
Max. Lamp Length (mm) - C/L	1514
Max. Lamp Diameter (mm) - D	28
Weight (kg)	0.28

Packaging

Single packaging type	Carton
Product EAN number	5410288271064
Packaging single length / height (cm)	158.0
Packaging single width (cm)	4.6
Packaging single depth (cm)	4.6

© Feilo Sylvania | Date Printed: 23 Nov 2018

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830


0027106

DUN14 (outer)	05410288271064
Units per outer package	10
Packaging outer length / height (cm)	160.5
Packaging outer width (cm)	25.9
Packaging outer depth (cm)	12.2


Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Suitable for accent lighting	Yes
Safety message	Suitable for totally enclosed fixture


PHOTOMETRY




TECHNICAL DRAWINGS










© Feilo Sylvania | Date Printed: 23 Nov 2018

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 3730LM 27W 830

0027106



© Feilo Sylvania | Date Printed: 23 Nov 2018