

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
0027108



Product features

- A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubes
- High performance glass construction design
- High lumen output - 4050lm, with an impressive lumen efficacy of 150 lm/W
- Omnidirectional light distribution (320°) and wide beam angle (220°)
- A++ energy rating and low power consumption
- Average rated life of 50'000 hours (L70 F50)
- Lamp length - 1500mm
- High power factor 0.95
- 200,000 switching cycle
- 5 years guarantee for complete peace of mind
- Colour temperature -6500K
- Suitable for outdoor applications in weather proof luminaires
- Compatible with electromagnetic gear and also suitable for direct mains operation (220-240V)
- No bending or discoloration over time
- No contactable metal parts, therefore no potential risk of electric shock



PRODUCT OVERVIEW

IPC Code	0027108
Product name	ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
Technology	LED
Watt (Rated) (W)	27
Lamp shape	LED Tubes T8
Cap/Base	G13
Lamp finish	Frosted
General application	Hospitality,Logistics & Industry,Residential & Consumer
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740528
E-number SE	8292594
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	4050
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	27
Average life (Nominal) (h)	50000
Product EAN number	5410288271088
Chromaticity coordinate Y	0.328

DATA TABLE

General data

IPC Code	0027108
Product name	ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
Technology	LED
Watt (Rated) (W)	27
Lamp shape	LED Tubes T8
Cap/Base	G13
Lamp finish	Frosted

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
0027108

General application	Hospitality,Logistics & Industry,Residential & Consumer
Operating temperature range (°C)	1500
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740528
E-number SE	8292594

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	4050
Luminous flux (Rated) (lm)	4050
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	27
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Control gear required	No
No. Of switching cycles before premature failures	200000
Transformer required	No
Drive current (mA)	120
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	27

Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

Nominal Product Diameter (mm)	1500
Max. Length base to base (mm) - A	1499
Length base to pin Min-Max (mm) - B	1513
Max. Lamp Diameter (mm) - D	28
Weight (kg)	0.28

Packaging

Single packaging type	Carton
Product EAN number	5410288271088
Packaging single length / height (cm)	158.0
Packaging single width (cm)	4.6

ToLEDo Superia T8 CCG and AC


ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
0027108

Packaging single depth (cm)	4.6
DUN14 (outer)	05410288271088
Units per outer package	10
Packaging outer length / height (cm)	160.5
Packaging outer width (cm)	25.9
Packaging outer depth (cm)	12.2





Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

PHOTOMETRY



TECHNICAL DRAWINGS



ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 865
0027108

