


Sylproof Tubular LED - Emergency 3 Hour

Sylproof Tubular LED 1X1500 EB NW E3
0047594



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

IPC Code	0047594
Product name	Sylproof Tubular LED 1X1500 EB NW E3
Technology	LED
Housing	Acrylic/PMMA Tube
Mount	Surface
Environment	Interior
General application	Logistics & Industry
Certifications	00
ETIM Class	EC000109
Fixture luminous flux (lm)	3352
Luminous flux (lm)	3352
Luminaire efficacy (lm/W)	106.07
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	0
Total power consumption (W)	32
Electrical protection	Class I
Control gear type	Electronic
Average life (Nominal) (h)	50000
Housing colour	Matt Diffuser
IP rating	IP66
IK rating	IK06
Product EAN number	5410288475943
Included lamp	INTEGRATED LED

DATA TABLE

General data

Sylproof Tubular LED - Emergency 3 Hour

Sylproof Tubular LED 1X1500 EB NW E3
0047594

IPC Code	0047594
Product name	Sylproof Tubular LED 1X1500 EB NW E3
Technology	LED
Housing	Acrylic/PMMA Tube
Mount	Surface
Environment	Interior
General application	Logistics & Industry
Operating temperature range (°C)	0 to +25
Certifications	00
ETIM Class	EC000109

Optical data

Fixture luminous flux (lm)	3352
Luminous flux (lm)	3352
Luminaire efficacy (lm/W)	106.07
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Distribution type	Direct
Photobiological Risk Group	0
Emergency duration (h)	3.0

Electrical data

Total power consumption (W)	32
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear type	Electronic
Drive current (mA)	400
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	24

Lifetime data

Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B10	49000
Lumen maintenance - L90 B50	35000
Average life (Nominal) (h)	50000

Physical data

Vertical Tilt (°)	360
Horizontal rotation (°)	360
Housing colour	Matt Diffuser
IP rating	IP66
IK rating	IK06

Sylproof Tubular LED - Emergency 3 Hour





Sylproof Tubular LED 1X1500 EB NW E3
0047594

Diffuser finish	Matt/Opaque
Diffuser material	Acrylic/PMMA
Nominal Product Length (mm)	1600
Nominal Product Width (mm)	112
Nominal Product Height (mm)	112
Weight (kg)	3.4

Packaging


Single packaging type	Carton
Product EAN number	5410288475943
Packaging single length / height (cm)	160.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0
DUN14 (outer)	05410288475943
Units per outer package	1
Packaging outer length / height (cm)	160.0
Packaging outer width (cm)	13.0
Packaging outer depth (cm)	13.0

PHOTOMETRY





TECHNICAL DRAWINGS

Sylproof Tubular LED - Emergency 3 Hour Sylproof Tubular LED 1X1500 EB NW E3 0047594





SYLVANIA 0047594


 This luminaire contains built in LED lamps.


 } LED


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.


 } LED

The lamps cannot be changed in the luminaire.

SYLVANIA 0047594  874/2012