

SylBay Gen 2 - DALI

SYLBAY 4000K SINGLE L2HO WIDE OPTIC DAL

0039986



Product features

- Logistics and Industry modular high bay luminaire with wide optics to provide homogenous light distribution for open space areas. Single body with 2 optical modules, 9,635 lumens, 64W, 151lm/W, 4000K, CRI 80, wide beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 410x386x133mm.



PRODUCT OVERVIEW

IPC Code	0039986
Product name	SYLBAY 4000K SINGLE L2HO WIDE OPTIC DAL
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC001716
E-number FI	4309008
Fixture luminous flux (lm)	9635
Luminaire efficacy (lm/W)	151
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Photobiological Risk Group	RG1
Total power consumption (W)	64
Electrical protection	Class I
Control gear type	DALI
Control gear mounting	Integral
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288399867
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

SylBay Gen 2 - DALI

SYLBAY 4000K SINGLE L2HO WIDE OPTIC DALI

0039986

General data

IPC Code	0039986
Product name	SYLBAY 4000K SINGLE L2HO WIDE OPTIC DALI
Technology	LED
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC001716
E-number FI	4309008

Optical data

Fixture luminous flux (lm)	9635
Luminaire efficacy (lm/W)	151
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	90
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	64
Mains voltage (V)	220-240V~
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	DALI
Control gear mounting	Integral
Dimmable	Yes
Drive current (mA)	700
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	11
Max. Luminaires per 13A C Breaker	16
Max. Luminaires per 16A C Breaker	20
Max. Luminaires per 20A C Breaker	25
Max. Luminaires per 10A B Breaker	7
Max. Luminaires per 13A B Breaker	10
Max. Luminaires per 16A B Breaker	12
Max. Luminaires per 20A B Breaker	15

Lifetime data

Lumen maintenance - L70 B50	50000
-----------------------------	-------

Physical data

Housing colour	Grey
----------------	------

SylBay Gen 2 - DALI

SYLBAY 4000K SINGLE L2HO WIDE OPTIC DALI


0039986

IP rating	IP65
IK rating	IK08
Diffuser finish	Polished
Diffuser material	Polycarbonate
Nominal Product Length (mm)	410
Nominal Product Width (mm)	386
Nominal Product Height (mm)	133
Weight (kg)	4.9

Packaging


Single packaging type	Carton
Product EAN number	5410288399867
Packaging single length / height (cm)	50.0
Packaging single width (cm)	50.0
Packaging single depth (cm)	21.0
DUN14 (outer)	05410288399867
Units per outer package	1
Packaging outer length / height (cm)	50.0
Packaging outer width (cm)	50.0
Packaging outer depth (cm)	21.0

PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.66	E(0°)	40.8°	20772
		E(C90)	40.8°	4753
		E(C0)	40.8°	4854
1.0	1.71	E(0°)	40.8°	5190
		E(C90)	40.8°	1183
		E(C0)	40.8°	1213
1.5	2.57	E(0°)	40.8°	2305
		E(C90)	40.8°	505
		E(C0)	40.8°	519
2.0	3.43	E(0°)	40.8°	1296
		E(C90)	40.8°	286
		E(C0)	40.8°	300
2.5	4.29	E(0°)	40.8°	831
		E(C90)	40.8°	189
		E(C0)	40.8°	194
3.0	5.14	E(0°)	40.8°	577
		E(C90)	40.8°	131
		E(C0)	40.8°	135


TECHNICAL DRAWINGS




SylBay Gen 2 - DALI


SYLBAY 4000K SINGLE L2HO WIDE OPTIC DALI
0039986


SYLVANIA 0039986


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

SYLVANIA 0039986  874/2012