

SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3

0045210



Product features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing (safety cable included), through wiring capability (TP6 = 6 core), sheet steel, 4189LM, 39W, 107lm/W, 4000K, drive current: 350mA, CRI 80, 138° wide beam angle, DALI dimmable, integral 3 hour maintained emergency, IP20, IK07, 50,000 hrs (L70), (LxWxH) 1505x66x76mm, 5 step MacAdam ellipse, 3.7kg, white RAL 9016, Class 1, 220-240V, energy class: A++, A+, A.



PRODUCT OVERVIEW

IPC Code	0045210
Product name	SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
Technology	LED
Housing	Sheet steel
Mount	Surface
Fixture rating	Enclosed
Environment	Internal
General application	Logistics & Industry
Certifications	EUNEW002
ETIM Class	EC000109
Fixture luminous flux (lm)	4189
Luminaire efficacy (lm/W)	99.73
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Colour Consistency (SDCM)	5
Beam Angle (°)	138
Glare control	29
Photobiological Risk Group	Exempt (Group 0)
Luminous flux (emergency) (lm)	450
Total power consumption (W)	42
Electrical protection	Class I
Control gear type	Electronic
Control gear mounting	Built-in
Dimmable	Yes
Minimum dimming level (%)	3
LED Flickering Rate	Medium (21% - 40%)
Average life (Nominal) (h)	50000
Housing colour	White RAL 9016
IP rating	IP20
IK rating	IK07

SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
0045210

Product EAN number	5410288452104
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0045210
Product name	SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
Technology	LED
Housing	Sheet steel
Mount	Surface
Fixture rating	Enclosed
Environment	Internal
General application	Logistics & Industry
Operating temperature range (°C)	0 to +25
Certifications	EUNEW002
ETIM Class	EC000109

Optical data

Fixture luminous flux (lm)	4189
Luminaire efficacy (lm/W)	99.73
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Colour Consistency (SDCM)	5
Adjustable chromaticity	N
Beam Angle (°)	138
Distribution type	Direct (symmetrical)
Glare control	29
Photobiological Risk Group	Exempt (Group 0)
Luminous flux (emergency) (lm)	450
Emergency duration (h)	3

Electrical data

Total power consumption (W)	42
Mains voltage (V)	220-240V~
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) = xx.x %	10
Electrical protection	Class I
Control gear type	Electronic
Control gear mounting	Built-in
Dimmable	Yes
Minimum dimming level (%)	3
Drive current (mA)	350
Inrush Current (A)	25

SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
0045210

Inrush Duration (µs)	177
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	Medium (21% - 40%)
Max. Luminaires per 10A C Breaker	32
Max. Luminaires per 13A C Breaker	42
Max. Luminaires per 16A C Breaker	53
Max. Luminaires per 20A C Breaker	66

Lifetime data

Lumen maintenance - L70 B50	50000
Lumen maintenance - L70 B20	30000
Lumen maintenance - L70 B10	15000
Lumen maintenance - L80 B50	30000
Lumen maintenance - L80 B20	30000
Lumen maintenance - L80 B10	15000
Lumen maintenance - L90 B50	15000
Lumen maintenance - L90 B20	15000
Lumen maintenance - L90 B10	15000
Average life (Nominal) (h)	50000

Physical data

Housing colour	White RAL 9016
IP rating	IP20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1505
Nominal Product Width (mm)	66
Nominal Product Height (mm)	76
Weight (kg)	3.7









Packaging

Single packaging type	Carton
Product EAN number	5410288452104
Packaging single length / height (cm)	152.0
Packaging single width (cm)	8.0
Packaging single depth (cm)	9.0
DUN14 (outer)	05410288452104
Units per outer package	1
Packaging outer length / height (cm)	152.0
Packaging outer width (cm)	8.0
Packaging outer depth (cm)	9.0

PHOTOMETRY

SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
0045210



SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3
0045210


TECHNICAL DRAWINGS

Version	L	H	W
600mm	600	76	66
1200mm	1205	76	66
1500mm	1505	76	66
1200mm PAR	1205	76	66
1500mm PAR	1505	76	66


0045210



This luminaire contains built in LED lamps.



The lamps cannot be changed in the luminaire.

874/2012


SylBatten LED - DALI

SYLBATTEN LED 1505MM 4000LM 4000K DALI (TP6) E3

0045210

