

## Hydroproof LED G3 Quick connector

### HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW

0048836



#### Product features

- Hydroproof, integrated LED chemical resistant weatherproof luminaire with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. GRP housing, PMMA diffuser, DALI dimmable, with MW sensor, 4000K, CRI80, 6900 lm, 48 W, 144 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK02, IP65.



#### PRODUCT OVERVIEW

IPC Code	0048836
Product name	HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW
Technology	LED
Housing	GRP
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW023
ETIM Class	EC000109
Fixture luminous flux (lm)	6900
Luminaire efficacy (lm/W)	144
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class I
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK02
Product EAN number	5410288488363
Lamps	Yes
Included lamp	INTEGRATED LED

## Hydroproof LED G3 Quick connector

*HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW*

0048836

### DATA TABLE

#### General data

IPC Code	0048836
Product name	HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW
Technology	LED
Housing	GRP
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +40°C
Certifications	EUNEW023
ETIM Class	EC000109

#### Optical data

Fixture luminous flux (lm)	6900
Luminaire efficacy (lm/W)	144
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Photobiological Risk Group	RG1

#### Electrical data

Total power consumption (W)	48
Mains voltage (V)	220-240V~
Mains frequency (Hz)	0/50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	DC/50/60Hz
Max. Luminaires per 10A C Breaker	21
Max. Luminaires per 13A C Breaker	28
Max. Luminaires per 16A C Breaker	36
Max. Luminaires per 20A C Breaker	45
Max. Luminaires per 10A B Breaker	13
Max. Luminaires per 13A B Breaker	17
Max. Luminaires per 16A B Breaker	22
Max. Luminaires per 20A B Breaker	27

## Hydroproof LED G3 Quick connector

*HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW*

0048836

### Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Average life (Nominal) (h)	50000

### Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK02
Diffuser finish	Clear
Diffuser material	PMMA
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78
Weight (kg)	2.71



### Packaging

Single packaging type	Carton
Product EAN number	5410288488363
Packaging single length / height (cm)	167.2
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288488363
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4

### Safety data


Dry applications use only	No
---------------------------	----

## PHOTOMETRY



## Hydroproof LED G3 Quick connector *HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW* 0048836

### TECHNICAL DRAWINGS



## Hydroproof LED G3 Quick connector

*HYDROPROOF LED G3 1500mm Twin 4K QC DALI MW*

0048836

