

Beacon LED Muse II

BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
2059740



Product features

- Integrated LED spotlight, black RAL 9005, unique soft-touch ring, adjustable beam angle from a 8° spot to a 55° flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 8° spot to 55° flood, optics: aspheric glass lens, colour temperature: 4000K neutral white, total system power: 21W, total fixture output: 1150lm, luminaire efficacy: 55lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B10, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, SylSmart SSC, power factor: 0.9 electrical protection: CLASS II, 1-circuit track adaptor, suitable for Concord Lytespan 1 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x135x153mm, weight: 0.95kg.



PRODUCT OVERVIEW

IPC Code	2059740
Product name	BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
Technology	LED
Housing	ALUMINIUM
Mount	TRACK
General application	Museums & Galleries
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4274031
Fixture luminous flux (lm)	623/1150
Luminaire efficacy (lm/W)	55
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	97
Colour Consistency (SDCM)	3
Photobiological Risk Group	1
Total power consumption (W)	21
Product Voltage (V)	240
Electrical protection	Class II
Dimmable	Yes
Housing colour	BLACK
IP rating	IP20
IK rating	IK02
Product EAN number	5025768597406
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

Beacon LED Muse II

BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
2059740

IPC Code	2059740
Product name	BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
Technology	LED
Housing	ALUMINIUM
Mount	TRACK
General application	Museums & Galleries
Operating temperature rated (°C)	25
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4274031

Optical data

Fixture luminous flux (lm)	623/1150
Luminaire efficacy (lm/W)	55
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	97
Colour Consistency (SDCM)	3
Photobiological Risk Group	1

Electrical data

Total power consumption (W)	21
Mains voltage (V)	230-240V~
Product Voltage (V)	240
Electrical protection	Class II
Dimmable	Yes
Inrush Current (A)	5
Inrush Duration (µs)	50
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	52
Max. Luminaires per 16A C Breaker	85

Lifetime data

Lumen maintenance - L70 B50	72000
-----------------------------	-------

Physical data

Housing colour	BLACK
IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	135
Nominal Product Height (mm)	153
Nominal Product Diameter (mm)	80
Weight (kg)	2.226

Packaging

Single packaging type	Carton
Product EAN number	5025768597406
Packaging single length / height (cm)	6.89

Beacon LED Muse II


BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
2059740

Packaging single width (cm)	5.906
Packaging single depth (cm)	6.89
DUN14 (outer)	05025768597406
Units per outer package	1
Packaging outer length / height (cm)	6.89
Packaging outer width (cm)	5.906
Packaging outer depth (cm)	6.89

Safety data


Dry applications use only	Yes
---------------------------	-----

PHOTOMETRY



Distance [m]	Cone diameter [m]	E _{0°} [lx]	E _{1/2°} [lx]	E _{1/4°} [lx]
0.5	0.07	96196	47914	
1.0	0.14	24049	11963	
1.5	0.21	10569	5313	
2.0	0.28	6012	2988	
2.5	0.35	3548	1913	
3.0	0.42	2672	1325	


Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 8.0°) Illuminance [lx]



Distance [m]	Cone diameter [m]	E _{0°} [lx]	E _{1/2°} [lx]	E _{1/4°} [lx]
0.5	0.52	8708	2391	
1.0	1.03	1877	596	
1.5	1.55	746	266	
2.0	2.06	419	149	
2.5	2.58	266	96	
3.0	3.10	196	66	

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 27.3°) Illuminance [lx]

TECHNICAL DRAWINGS



Beacon LED Muse II

BEACON LED MUSE II 97CRI 4000K L1 SSC01 BLACK
2059740

