Start Flat Panel LED

START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2

0047647



Product features

- Edge lit LED flat panel HE (high efficiency). Low Flicker, 36 W, Neutral White, 4000 K, 4200 lumens, 120 lm/W, 50000 hours lifetime (L70), PMMA opal diffuser, aluminium frame, steel body, DALI dimmable driver. (HxWxD) 10.5 x 595 x 595 mm

PRODUCT OVERVIEW

IPC Code	0047647
Product name	START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW008
ETIM Class	EC002892
E-number FI	4274133
Fixture luminous flux (lm)	4200
Luminaire efficacy (lm/W)	120
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Glare control	<22
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class II
Control gear type	Electronic
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	50000
Housing colour	White
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288476476
Lamps	Yes
Included lamp	INTEGRATED LED

© Feilo Sylvania | Date Printed: 04 Dec 2018

Start Flat Panel LED

START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2

0047647

DATA TABLE

General data

IPC Code	0047647
Product name	START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW008
ETIM Class	EC002892
E-number FI	4274133

Optical data

Fixture luminous flux (lm)	4200
Luminaire efficacy (lm/W)	120
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam angle (Rated) (°)	110
Glare control	<22
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	36
Mains voltage (V)	220-240V~
Lamp power factor	0.98
Electrical protection	Class II
Control gear type	Electronic
Dimmable	Yes
Drive current (mA)	1200
Inrush Current (A)	23.3
Inrush Duration (µs)	192
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	20
Max. Luminaires per 10A B Breaker	12
Max. Luminaires per 16A B Breaker	19

Lifetime data

Lumen maintenance - L70 B50	50000
Average life (Nominal) (h)	50000

Physical data

Housing colour	White

© Feilo Sylvania | Date Printed: 04 Dec 2018

Start Flat Panel LED

START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2

0047647

IP rating	IP40/20
IK rating	IK03
Diffuser material	PMMA
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	10.5
Weight (kg)	3.004


Packaging

Single packaging type	Carton
Product EAN number	5410288476476
Packaging single length / height (cm)	68.6
Packaging single width (cm)	62.5
Packaging single depth (cm)	3.3
DUN14 (outer)	15410288476473
Units per outer package	2
Packaging outer length / height (cm)	71.1
Packaging outer width (cm)	65.7
Packaging outer depth (cm)	10.0


Safety data

Optimal operating condition (°C)	-10-40

PHOTOMETRY



TECHNICAL DRAWINGS





© Feilo Sylvania | Date Printed: 04 Dec 2018

Start Flat Panel LED

START FLAT PANEL LED HIGH EFFICIENCY 600 4000K DALI G2

0047647





© Feilo Sylvania | Date Printed: 04 Dec 2018