

Start Flat Panel LED UGR19

START FLAT PANEL UGR19 625 4000K G2

0047578



Product features

- Edge lit LED flat low glare panel (UGR<19). Low Flicker, 33 W, Neutral White, 4000 K, 3400 lumens, 103 lm/W, 50000 hours lifetime (L70), PMMA opal diffuser, aluminium frame, steel body, electronic non dimmable driver. (HxWxD) 10.5 x 595 x 595 mm



PRODUCT OVERVIEW

IPC Code	0047578
Product name	START FLAT PANEL UGR19 625 4000K G2
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Education, Hospitality, Office, Retail
Certifications	EUNEW008
ETIM Class	EC002892
Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Glare control	<19
Photobiological Risk Group	RG0
Total power consumption (W)	33
Electrical protection	Class II
Control gear type	Electronic
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	50000
Housing colour	White
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288475783
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

Start Flat Panel LED UGR19

START FLAT PANEL UGR19 625 4000K G2

0047578

General data

IPC Code	0047578
Product name	START FLAT PANEL UGR19 625 4000K G2
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Internal
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW008
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam angle (Rated) (°)	90
Glare control	<19
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	33
Mains voltage (V)	220-240V~
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	Electronic
Dimmable	No
Drive current (mA)	900
Inrush Current (A)	13
Inrush Duration (µs)	400
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	25
Max. Luminaires per 10A B Breaker	15
Max. Luminaires per 16A B Breaker	24

Lifetime data

Lumen maintenance - L70 B50	50000
Average life (Nominal) (h)	50000

Physical data

Housing colour	White
IP rating	IP40/20
IK rating	IK03
Diffuser material	PMMA/MS
Nominal Product Length (mm)	595

Start Flat Panel LED UGR19

START FLAT PANEL UGR19 625 4000K G2

0047578

Nominal Product Width (mm)	595
Nominal Product Height (mm)	10.5
Weight (kg)	3.082


Packaging

Single packaging type	Carton
Product EAN number	5410288475783
Packaging single length / height (cm)	71.13
Packaging single width (cm)	65.23
Packaging single depth (cm)	3.83
DUN14 (outer)	15410288475780
Units per outer package	2
Packaging outer length / height (cm)	72.7
Packaging outer width (cm)	68.0
Packaging outer depth (cm)	10.1


Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

PHOTOMETRY





TECHNICAL DRAWINGS




Start Flat Panel LED UGR19 START FLAT PANEL UGR19 625 4000K G2 0047578


SYLVANIA 0047578


 This luminaire contains built in LED lamps.

 } **LED**


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

SYLVANIA 0047578  874/2012