


Optix Recessed 600x600 Medium Output

OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI
0044164



Product features

- OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI is a high efficacy low glare luminaire for office and education applications with excellent colour rendering. Ceiling recessed 600x600 mm. Aluminised plastic extra low glare optics in 2 lines configuration. White RAL9016 fixture body. DALI dimmable. 4000K Neutral White LED, CRI>90, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 3550lm. Power consumption 30W. Luminaire efficacy 118lm/W. Lumen maintenance of L90B50 = 44000h, L90B10 = 39000h. UGR<16, Luminance at 65°<200 Cd/m², IK07, IP20. Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C.



PRODUCT OVERVIEW

IPC Code	0044164
Product name	OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI
Technology	LED (3 SDCM)
Housing	STEEL
Mount	Recessed
Fixture rating	Enclosed
General application	Office, Education,
Certifications	EUNEW008
ETIM Class	EC002892
Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	118
Colour temperature (K)	4000
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Glare control	16
Photobiological Risk Group	1
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	DALI
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9015
IP rating	IP20
IK rating	IK07
Product EAN number	5410288441641
Chromaticity coordinate Y	0.3797
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0044164
Product name	OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI

Optix Recessed 600x600 Medium Output

OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI

0044164

Technology	LED (3 SDCM)
Housing	STEEL
Mount	Recessed
Fixture rating	Enclosed
General application	Office, Education,
Certifications	EUNEW008
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	118
Colour temperature (K)	4000
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Glare control	16
Photobiological Risk Group	1

Electrical data

Total power consumption (W)	30
Starting time (max) (s)	<0.7
Mains voltage (V)	220-240V~
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) = xx.x %	9
Electrical protection	Class I
Control gear required	No
Control gear type	DALI
Dimmable	Yes
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	21
Max. Luminaires per 13A C Breaker	28
Max. Luminaires per 16A C Breaker	36
Max. Luminaires per 20A C Breaker	45
Max. Luminaires per 10A B Breaker	13
Max. Luminaires per 13A B Breaker	17
Max. Luminaires per 16A B Breaker	22
Max. Luminaires per 20A B Breaker	27

Lifetime data

Lumen maintenance - L70 B50	72000
Lumen maintenance - L80 B10	72000
Lumen maintenance - L90 B50	44000
Lumen maintenance - L90 B20	41000
Lumen maintenance - L90 B10	39000

Optix Recessed 600x600 Medium Output

OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI

0044164



Physical data

Housing colour	RAL 9015
IP rating	IP20
IK rating	IK07
Diffuser finish	Satin
Diffuser material	Polycarbonate
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Nominal Product Height (mm)	38
Weight (kg)	5.0


Packaging

Single packaging type	Carton
Product EAN number	5410288441641
Packaging single length / height (cm)	62.0
Packaging single width (cm)	6.5
Packaging single depth (cm)	65.0
DUN14 (outer)	05410288441641
Units per outer package	1
Packaging outer length / height (cm)	62.0
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	65.0

PHOTOMETRY



TECHNICAL DRAWINGS



Optix Recessed 600x600 Medium Output OPTIX RECESSED 600x600 2L 4000K C9 ALU DALI 0044164

SYLVANIA 0044164

 This luminaire contains built in LED lamps.


 } LED

The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.


 } LED

The lamps cannot be changed in the luminaire.

SYLVANIA 0044164  874/2012