

Product features



LED back-lit recessed IP44 panel, 4000K Neutral White, 4200lm delivered from 30W, 140lm/W total system effciency, energy efficient external driver included as standard, even distribution of light throughout fixture, long lifetime of 50,000 hours (L70), size (HxWxD) 620x620x65mm.











PRODUCT OVERVIEW

IPC Code	0047789
Product name	START PANEL 625 4000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office, Hospitality, Retail, Education,
Certifications	EUNEW008
ETIM Class	EC002892
Fixture luminous flux (Im)	4200
Luminaire efficacy (lm/W)	140
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Glare control	<25
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class II
Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Product EAN number	5410288477893
Lamps	Yes

DATA TABLE

General data	
IPC Code	0047789
Product name	START PANEL 625 4000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office, Hospitality, Retail, Education,
Certifications	EUNEW008
ETIM Class	EC002892



\sim		
()	ntical	Ctch.
\sim	pucai	data

Fixture luminous flux (lm)	4200
Luminaire efficacy (Im/W)	140
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam angle (Rated) (°)	107
Glare control	<25
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	30
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class II
Drive current (mA)	130
Inrush Current (A)	22
Inrush Duration (µs)	250
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	45
Max. Luminaires per 13A C Breaker	58
Max. Luminaires per 16A C Breaker	72
Max. Luminaires per 20A C Breaker	90

Lifetime data

Physical data


Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Nominal Product Length (mm)	620
Nominal Product Width (mm)	620
Nominal Product Height (mm)	63
Weight (kg)	2.83


Packaging

Single packaging type	Carton
Product EAN number	5410288477893
Packaging single length / height (cm)	64.1
Packaging single width (cm)	65.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288477893
Units per outer package	1
Packaging outer length / height (cm)	64.1
Packaging outer width (cm)	65.0
Packaging outer depth (cm)	8.5



PHOTOMETRY





TECHNICAL DRAWINGS

