

Start Panel LED HO

START PANEL HO 600 3000K G4
0047780



Product features

- LED back-lit recessed IP44 panel (high output), 3000K Warm White, 4500lm delivered from 36W, 125lm/W total system efficiency, energy efficient external driver included as standard, even distribution of light throughout fixture, long lifetime of 50,000 hours (L70), size (HxWxD) 596x596x65mm.



PRODUCT OVERVIEW

IPC Code	0047780
Product name	START PANEL HO 600 3000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW008
ETIM Class	EC002892
E-number FI	4274184
Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	125
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Glare control	<25
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class II
Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Product EAN number	5410288477800
Lamps	Yes
Included lamp	0

DATA TABLE

General data

IPC Code	0047780
Product name	START PANEL HO 600 3000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW008

Start Panel LED HO

START PANEL HO 600 3000K G4
0047780

ETIM Class	EC002892
E-number FI	4274184

Optical data

Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	125
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam angle (Rated) (°)	107
Glare control	<25
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	36
Mains voltage (V)	220-240V~
Lamp power factor	0.97
Electrical protection	Class II
Drive current (mA)	155
Inrush Current (A)	22
Inrush Duration (µs)	250
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	38
Max. Luminaires per 13A C Breaker	48
Max. Luminaires per 16A C Breaker	60
Max. Luminaires per 20A C Breaker	75

Lifetime data

Lumen maintenance - L70 B50	50000
Lumen maintenance - L80 B10	30000

Physical data

Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Nominal Product Height (mm)	63
Weight (kg)	2.6


Packaging

Single packaging type	Carton
Product EAN number	5410288477800
Packaging single length / height (cm)	63.0
Packaging single width (cm)	61.5
Packaging single depth (cm)	7.6
DUN14 (outer)	05410288477800
Units per outer package	1
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	61.5


Start Panel LED HO
START PANEL HO 600 3000K G4
0047780

Packaging outer depth (cm) 7.6

PHOTOMETRY



TECHNICAL DRAWINGS



Start Panel LED HO START PANEL HO 600 3000K G4 0047780

