

Product features



LED back-lit recessed IP44 panel (high output), 4000K Warm White, 4750lm delivered from 36W, 132lm/W total system effciency, energy efficient external driver included as standard, even distribution of light throughout fixture, long lifetime of 50,000 hours (L70), size (HxWxD) 620x620x65mm.











PRODUCT OVERVIEW

IPC Code	0047791
Product name	START PANEL HO 625 4000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office, Hospitality, Retail, Education,
Certifications	EUNEW008
ETIM Class	EC002892
Fixture luminous flux (Im)	4750
Luminaire efficacy (lm/W)	135
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Glare control	<25
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class II
Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Product EAN number	5410288477916
Lamps	Yes

DATA TABLE

General data	
IPC Code	0047791
Product name	START PANEL HO 625 4000K G4
Technology	LED
Housing	Steel
Mount	Recessed
General application	Office, Hospitality, Retail, Education,
Certifications	EUNEW008
ETIM Class	EC002892



Optical data	
Fixture luminous flux (lm)	4750
Lumain aine affica au (Inc (A))	105

Luminaire efficacy (Im/W) 135
CRI (Ra) 80
Colour Variation Initial (SDCM) 6
Beam angle (Rated) (°) 107

Glare control <25
Photobiological Risk Group RG0

Electrical data

Total power consumption (W) 36 Mains voltage (V) 220-240V~ Lamp power factor 0.97 **Electrical protection** Class II Drive current (mA) 155 22 Inrush Current (A) 250 Inrush Duration (µs) Nominal Frequency (Hz) 50/60Hz Max. Luminaires per 10A C Breaker 38 Max. Luminaires per 13A C Breaker 48 60 Max. Luminaires per 16A C Breaker Max. Luminaires per 20A C Breaker 75

Lifetime data

Lumen maintenance - L70 B50 50000

Physical data


Housing colour	White RAL9016
IP rating	IP44
IK rating	IK03
Nominal Product Length (mm)	620
Nominal Product Width (mm)	620
Nominal Product Height (mm)	63
Weight (kg)	2.882


Packaging

Single packaging type	Carton
Product EAN number	5410288477916
Packaging single length / height (cm)	64.1
Packaging single width (cm)	65.0
Packaging single depth (cm)	7.6
DUN14 (outer)	05410288477916
Units per outer package	1
Packaging outer length / height (cm)	64.1
Packaging outer width (cm)	65.0
Packaging outer depth (cm)	7.6



PHOTOMETRY





TECHNICAL DRAWINGS

