Syl-lighter LED II 240

SYL-LIGHTER II 240 25W NW DALI

3031848



Product features

- Ceiling recessed IP44 from the front LED downlight, perfect where limited ceiling void is available with only 65mm product depth and 225mm cutout. Ideal replacement for 2x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminiares. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 2408LM, 25W, 96lm/W, 4000K, Driver Current: 650mA, CRI80, 74° beam angle, Dali dimmable LED driver, IP44 from the front, IK07, 50,000 hrs (L70), (HxW) 65x225mm, 5 step MacAdam ellipse, 0.65kg, RAL9003, Class 2, 220-240V, energy class: A++, A+, A

PRODUCT OVERVIEW

IPC Code	3031848
Product name	SYL-LIGHTER II 240 25W NW DALI
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Interior
General application	Hospitality
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4270294
E-number SE	7470974
Fixture luminous flux (lm)	2408
Luminaire efficacy (lm/W)	96
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Photobiological Risk Group	RG0
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	Dimmable
Control gear mounting	Remote
Dimmable	Yes
Minimum dimming level (%)	1
Average life (Nominal) (h)	50000
Housing colour	White - RAL9003
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971318484
Lamps	No
Included lamp	INTEGRATED LED

© Feilo Sylvania | Date Printed: 06 Dec 2018

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W NW DALI

3031848

DATA TABLE

General data

IPC Code	3031848
Product name	SYL-LIGHTER II 240 25W NW DALI
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Interior
General application	Hospitality
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4270294
E-number SE	7470974

Optical data

Fixture luminous flux (lm)	2408
Luminaire efficacy (lm/W)	96
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Beam angle (Rated) (°)	74
Distribution type	Direct - Symmetrical
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	25
Mains voltage (V)	220-240V~
Lamp power factor	0.96
Electrical protection	Class II
Control gear required	Yes
Control gear type	Dimmable
Control gear mounting	Remote
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	650
Inrush Current (A)	26
Inrush Duration (µs)	151
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	31
Max. Luminaires per 13A C Breaker	43
Max. Luminaires per 16A C Breaker	53
Max. Luminaires per 20A C Breaker	66
Max. Luminaires per 10A B Breaker	19
Max. Luminaires per 13A B Breaker	26

© Feilo Sylvania | Date Printed: 06 Dec 2018

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W NW DALI

3031848

Max. Luminaires per 16A B Breaker	32
Max. Luminaires per 20A B Breaker	40

Lifetime data

Lumen maintenance - L70 B50	50000
Average life (Nominal) (h)	50000


Physical data


Housing colour	White - RAL9003
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	Polycarbonate
Reflector finish	Diffuser
Nominal Product Height (mm)	65
Nominal Product Diameter (mm)	240
Weight (kg)	0.849

Packaging

Single packaging type	Carton
Product EAN number	8711971318484
Packaging single length / height (cm)	27.6
Packaging single width (cm)	27.3
Packaging single depth (cm)	8.1
DUN14 (outer)	18711971318484
Units per outer package	12
Packaging outer length / height (cm)	56.3
Packaging outer width (cm)	56.5
Packaging outer depth (cm)	27.3

PHOTOMETRY






TECHNICAL DRAWINGS


© Feilo Sylvania | Date Printed: 06 Dec 2018

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W NW DALI

3031848






© Feilo Sylvania | Date Printed: 06 Dec 2018

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W NW DALI

3031848



© Feilo Sylvania | Date Printed: 06 Dec 2018