


## Syl-lighter LED II 220

*Syl-Lighter LED II 220 RO 21W NW*  
3031817



### Product features

- Ceiling recessed IP44 from the front LED downlight, perfect where limited ceiling void is available with only 60mm product depth and 205mm cutout. Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 1989LM, 21W, 95lm/W, 4000K, Driver Current: 600mA, CRI80, 74° beam angle, Non-dimmable LED driver, IP44 from the front, IK07, 50,000 hrs (L70), (HxW) 60x205mm, 5 step MacAdam ellipse, 0.60kg, RAL9003, Class 2, 220-240V, energy class: A++, A+, A



### PRODUCT OVERVIEW

IPC Code	3031817
Product name	Syl-Lighter LED II 220 RO 21W NW
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Interior
General application	Hospitality
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4271256
E-number SE	7467167
Fixture luminous flux (lm)	1989
Luminaire efficacy (lm/W)	95
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	74
Glare control	23.7
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	Electronic
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	50000
Housing colour	White (RAL 9003)
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971318170
Lamps	Yes
Included lamp	INTEGRATED LED

## Syl-lighter LED II 220

*Syl-Lighter LED II 220 RO 21W NW*  
3031817

### DATA TABLE

#### General data

IPC Code	3031817
Product name	Syl-Lighter LED II 220 RO 21W NW
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Environment	Interior
General application	Hospitality
Operating temperature range (°C)	-10 to +40
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4271256
E-number SE	7467167

#### Optical data

Fixture luminous flux (lm)	1989
Luminaire efficacy (lm/W)	95
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Adjustable chromaticity	N
Beam Angle (°)	74
Distribution type	Direct - Symmetrical
Glare control	23.7
Photobiological Risk Group	RG0

#### Electrical data

Total power consumption (W)	21
Mains voltage (V)	220-240V~
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class II
Control gear type	Electronic
Dimmable	No
Drive current (mA)	600
Inrush Current (A)	6.44
Inrush Duration (µs)	830
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	12
Max. Luminaires per 13A C Breaker	15
Max. Luminaires per 16A C Breaker	19
Max. Luminaires per 20A C Breaker	25

## Syl-lighter LED II 220

*Syl-Lighter LED II 220 RO 21W NW*

3031817

### Lifetime data

Lumen maintenance - L70 B50	50000
Lumen maintenance - L70 B20	38000
Lumen maintenance - L70 B10	35000
Lumen maintenance - L80 B50	28000
Lumen maintenance - L80 B20	24000
Lumen maintenance - L80 B10	22000
Lumen maintenance - L90 B50	14000
Lumen maintenance - L90 B20	11000
Lumen maintenance - L90 B10	10000
Average life (Nominal) (h)	50000

### Physical data

Housing colour	White (RAL 9003)
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	Polycarbonate
Reflector finish	Mirror
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	220
Weight (kg)	0.72
Recessed Depth (mm)	150

### Packaging

Single packaging type	Carton
Product EAN number	8711971318170
Packaging single length / height (cm)	25.0
Packaging single width (cm)	25.0
Packaging single depth (cm)	7.5
DUN14 (outer)	18711971318177
Units per outer package	12
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	52.0
Packaging outer depth (cm)	26.0

## PHOTOMETRY



## Syl-lighter LED II 220 Syl-Lighter LED II 220 RO 21W NW 3031817

**Lumiance** 3031817

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

**Lumiance** 3031817  874/2012