

Tide - Track Version - High Output


TIDE HO DASYM 93 4K L3

2059842



Product features

- Linear LED Luminaire for lighting of large wall surfaces and artifacts in art galleries and museums providing outstanding horizontal and vertical uniformity combined with high colour rendering index. Light distribution: Double Asymmetric, color temperature: 4000K , total system power: 40W, total fixture output: 2576lm, luminaire efficacy: 64lm/W, LOR: 100%, colour rendering index: 90 (93 typical), LED Chromaticity: 3 step MacAdam ellipse tolerance, lifetime: 60000 hours at L70B50, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, Switched, power factor: 0.98, electrical protection: Class I, Lytespan 3 - Three Circuit Adaptor, ingress protection rating: IP20 , suitable for internal environment only, dimensions: 604x37x46mm, the housing is made of Aluminium in White - RAL9016 color, Net weight is 0.82kg.



PRODUCT OVERVIEW

IPC Code	2059842
Product name	TIDE HO DASYM 93 4K L3
Technology	LED
Housing	Aluminium
Mount	L3 Track
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries
Certifications	EUNEW009
ETIM Class	EC001744
Fixture luminous flux (lm)	2576
Luminaire efficacy (lm/W)	64
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	40
Electrical protection	Class I
Control gear type	Electronic
Control gear mounting	Integral
Dimmable	N
Housing colour	White - RAL9016
IP rating	IP20
IK rating	IK02
Product EAN number	5025768598427
Lamps	No
Included lamp	Integrated LED

Tide - Track Version - High Output

TIDE HO DASYM 93 4K L3
2059842

DATA TABLE

General data

IPC Code	2059842
Product name	TIDE HO DASYM 93 4K L3
Technology	LED
Housing	Aluminium
Mount	L3 Track
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries
Certifications	EUNEW009
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	2576
Luminaire efficacy (lm/W)	64
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Distribution type	Double Asymmetric
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	40
Mains voltage (V)	220-240V~
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	Yes
Control gear type	Electronic
Control gear mounting	Integral
Dimmable	N
Drive current (mA)	500
Inrush Current (A)	20
Inrush Duration (µs)	170
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	12
Max. Luminaires per 16A C Breaker	20

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L90 B50	60000

Physical data

Housing colour	White - RAL9016
----------------	-----------------

Tide - Track Version - High Output

TIDE HO DASYM 93 4K L3


2059842

IP rating	IP20
IK rating	IK02
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	604
Nominal Product Width (mm)	37
Nominal Product Height (mm)	46
Weight (kg)	0.82


Packaging

Single packaging type	Carton
Product EAN number	5025768598427
Packaging single length / height (cm)	71.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	5.5
DUN14 (outer)	05025768598427
Units per outer package	1
Packaging outer length / height (cm)	71.0
Packaging outer width (cm)	5.5
Packaging outer depth (cm)	5.5

PHOTOMETRY



TECHNICAL DRAWINGS



Tide - Track Version - High Output

TIDE HO DASYM 93 4K L3
2059842

