

RouteLED 2

ROUTELED II CORRIDOR

2059460



Product features

- Miniature emergency recessed luminaire downlight with corridor optic, non-maintained 3 hr emergency, standalone unit with inverter module and rechargeable battery (NiMH), quick and easy installation with inverter module and battery pack contained in articulated case that can pass through 40mm cutout, 219lm, 3W, IK07, beam angle 148 degrees, 230V, 50-60Hz, recharge period 24 hours, Power Factor 0.45, charge current 300mA, LxWxD (mm) 416x29x26.



PRODUCT OVERVIEW

IPC Code	2059460
Product name	ROUTELED II CORRIDOR
Technology	LED
Housing	ALUMINIUM
Mount	CEILING RECESSED
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW001
ETIM Class	EC001957
Fixture luminous flux (lm)	212
LOR (%)	100
Colour temperature (K)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Variation Initial (SDCM)	5
Colour Consistency (SDCM)	5
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Total power consumption (W)	2
Product Voltage (V)	230
Electrical protection	Class II
Average life (Nominal) (h)	60000
Housing colour	WHITE - RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768594603
Luminous flux (emergency) (lm)	219
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

RouteLED 2

ROUTELED II CORRIDOR

2059460

IPC Code	2059460
Product name	ROUTELED II CORRIDOR
Technology	LED
Housing	ALUMINIUM
Mount	CEILING RECESSED
General application	Office,Hospitality,Retail,Education,
Operating temperature rated (°C)	25
Certifications	EUNEW001
ETIM Class	EC001957

Optical data

Fixture luminous flux (lm)	212
LOR (%)	100
Colour temperature (K)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Variation Initial (SDCM)	5
Colour Consistency (SDCM)	5
Beam angle (Rated) (°)	158
Distribution type	DIRECT
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Emergency duration (h)	3

Electrical data

Total power consumption (W)	2
Mains voltage (V)	230-240V~
Product Voltage (V)	230
Electrical protection	Class II
Drive current (mA)	200
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	60000
----------------------------	-------

Physical data

Housing colour	WHITE - RAL9016
IP rating	IP20
IK rating	IK07
Nominal Product Length (mm)	416
Nominal Product Width (mm)	27
Nominal Product Height (mm)	27
Weight (kg)	0.948
Recessed Depth (mm)	80

Packaging

Single packaging type	Carton
Product EAN number	5025768594603

RouteLED 2

ROUTELED II CORRIDOR


2059460

Packaging single length / height (cm)	8.268
Packaging single width (cm)	7.087
Packaging single depth (cm)	4.134
DUN14 (outer)	0
Units per outer package	1
Packaging outer length / height (cm)	8.268
Packaging outer width (cm)	7.087
Packaging outer depth (cm)	4.134

Safety data

Dry applications use only	Yes
---------------------------	-----

PHOTOMETRY



TECHNICAL DRAWINGS

