SylSafe IP65 LED

Syl Safe IP65 LED Recessed with Exit Sign Arrow Down

9153908



Product features

- Recessed LED Emergency maintained luminaire with hanging blade exit legend with arrow pointing down. Available with 16 x White LEDs. Includes Ni-Cad batteries (3.6V 1.8Ah NiCd). Supply power 6.5W (1.7W charging) 230V and 50Hz.

PRODUCT OVERVIEW

IPC Code	9153908
Product name	Syl Safe IP65 LED Recessed with Exit Sign Arrow Down
Technology	LED
Environment	Internal
General application	Education,Hospitality,Office,Retail
Fixture luminous flux (lm)	135
Total power consumption (W)	6.5
Electrical protection	Class I
IP rating	IP65
Luminous flux (emergency) (lm)	135

DATA TABLE

General data

IPC Code	9153908
Product name	Syl Safe IP65 LED Recessed with Exit Sign Arrow Down
Technology	LED
Environment	Internal
General application	Education,Hospitality,Office,Retail

Optical data

Fixture luminous flux (lm)	135
Adjustable chromaticity	N
Emergency duration (h)	3

Electrical data

Total power consumption (W)	6.5
Mains voltage (V)	230V~
Electrical protection	Class I
Transformer required	Yes

© Feilo Sylvania | Date Printed: 13 Dec 2018

SylSafe IP65 LED

Syl Safe IP65 LED Recessed with Exit Sign Arrow Down

9153908


Physical data

IP rating	IP65
Nominal Product Length (mm)	420
Nominal Product Width (mm)	165
Nominal Product Height (mm)	160
Weight (kg)	2.0
Recessed Depth (mm)	85

Packaging

Single packaging type	Carton
Packaging single length / height (cm)	39.0
Packaging single width (cm)	19.0
Packaging single depth (cm)	7.0
Units per outer package	1
Packaging outer length / height (cm)	39.0
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	7.0

TECHNICAL DRAWINGS



© Feilo Sylvania | Date Printed: 13 Dec 2018