SylSafe IP65 LED

SYLSAFE IP65 LED M3 DALI/SELF TEST

9154052



Product features

- Maintained LED emergency luminaire with DALI/Self Test function (BSEN62034), IP65 polycarbonate body, 3 hour emergency duration, integral NiCD batteries (1 x 3.6V 1.8AH NiCD), 135lm, 7W (1.7W Charge).

PRODUCT OVERVIEW

IPC Code	9154052
Product name	SYLSAFE IP65 LED M3 DALI/SELF TEST
Housing	Polycarbonate
Mount	Ceiling Mounting
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW002
Fixture luminous flux (lm)	135
Colour temperature (K)	4000
Light colour	Neutral White
Total power consumption (W)	7
Electrical protection	Class II
Average life (Nominal) (h)	50000
Housing colour	White
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	9154052
Product name	SYLSAFE IP65 LED M3 DALI/SELF TEST
Housing	Polycarbonate
Mount	Ceiling Mounting
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW002

Optical data

Fixture luminous flux (lm)	135
Colour temperature (K)	4000
Light colour	Neutral White
Adjustable chromaticity	N
Emergency duration (h)	3

© Feilo Sylvania | Date Printed: 13 Dec 2018

SylSafe IP65 LED

SYLSAFE IP65 LED M3 DALI/SELF TEST

9154052

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V~
Electrical protection	Class II

Lifetime data

Average life (Nominal) (h)	50000


Physical data

Housing colour	White
Nominal Product Length (mm)	350
Nominal Product Width (mm)	120
Nominal Product Height (mm)	90
Weight (kg)	2.65

Packaging

Single packaging type	Carton
Packaging single length / height (cm)	38.0
Packaging single width (cm)	15.0
Packaging single depth (cm)	11.0
Units per outer package	1
Packaging outer length / height (cm)	38.0
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	11.0

TECHNICAL DRAWINGS



© Feilo Sylvania | Date Printed: 13 Dec 2018