

## SylSafe Spot

*SylSafe Spot RA R EM3 NM MS*  
0041720



### Product features

- SylSafe Spot RA R EM3 NM MS is a miniature emergency recessed downlight with interchangeable optics for open area and escape route illumination. Non-maintained 3 hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. Quick and easy installation with driver module and battery pack contained in articulated case that can pass through 40mm cutout. 160lm, 3W, IK03, IP30. Power Factor 0.45. Class II electrical construction.



## PRODUCT OVERVIEW

IPC Code	0041720
Product name	SylSafe Spot RA R EM3 NM MS
Technology	LED
Type	LED
Mount	Recessed
General application	Office,Hospitality,Retail,Museums & Galleries,Education
Certifications	EUNEW001
ETIM Class	EC001957
Fixture luminous flux (lm)	160
Luminaire efficacy (lm/W)	53
Colour temperature (K)	6300
CRI (Ra)	75
Photobiological Risk Group	RG02
Luminous flux (emergency) (lm)	160
Total power consumption (W)	3
Electrical protection	Class II
Control gear type	Emergency (3 hour non-maintained)
Dimmable	N
Average life (Nominal) (h)	35040
Housing colour	White
IP rating	IP30
IK rating	IK03
Product EAN number	5410288417202
Lamps	No
Included lamp	INTEGRATED LED

## DATA TABLE

### General data

IPC Code	0041720
Product name	SylSafe Spot RA R EM3 NM MS

## SylSafe Spot

*SylSafe Spot RA R EM3 NM MS*  
0041720

Technology	LED
Type	LED
Mount	Recessed
General application	Office,Hospitality,Retail,Museums & Galleries,Education
Certifications	EUNEW001
ETIM Class	EC001957

### Optical data

Fixture luminous flux (lm)	160
Luminaire efficacy (lm/W)	53
Colour temperature (K)	6300
CRI (Ra)	75
Distribution type	Corridor / Area selectable
Photobiological Risk Group	RG02
Luminous flux (emergency) (lm)	160
Emergency duration (h)	3

### Electrical data

Total power consumption (W)	3
Mains voltage (V)	230-240V~
Lamp power factor	0.45
Electrical protection	Class II
Control gear required	Yes
Control gear type	Emergency (3 hour non-maintained)
Dimmable	N
Drive current (mA)	30
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	35040
----------------------------	-------

### Physical data

Housing colour	White
IP rating	IP30
IK rating	IK03
Nominal Product Length (mm)	50
Nominal Product Width (mm)	50
Nominal Product Height (mm)	45
Weight (kg)	0.32

### Packaging





Single packaging type	Carton
Product EAN number	5410288417202
Packaging single length / height (cm)	21.0
Packaging single width (cm)	9.3
Packaging single depth (cm)	4.7
DUN14 (inner)	05410288417202
DUN14 (outer)	05410288417202

## SylSafe Spot


SylSafe Spot RA R EM3 NM MS  
0041720

Units per outer package	25
Packaging outer length / height (cm)	42.4
Packaging outer width (cm)	29.8
Packaging outer depth (cm)	28.0

### PHOTOMETRY



### TECHNICAL DRAWINGS



## SylSafe Spot SylSafe Spot RA R EM3 NM MS 0041720

**SYLVANIA** 0041720

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

**SYLVANIA** 0041720  874/2012