

SylSafe Spot

SylSafe Spot RA C EM3 NM DA
0041730



Product features

- SylSafe Spot RA C EM3 NM DA is a miniature emergency surface mounted downlight with interchangeable optics for open area and escape route illumination. Non-maintained 3 hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. Self testing with DALI monitoring capability. 145lm, 1.8W, IK03, IP40. Power Factor 0.44. Class II electrical construction.



PRODUCT OVERVIEW

IPC Code	0041730
Product name	SylSafe Spot RA C EM3 NM DA
Technology	LED
Type	LED
Mount	Surface mounted
General application	Office,Hospitality,Retail,Museums & Galleries,Education
Certifications	EUNEW002
ETIM Class	EC001957
Fixture luminous flux (lm)	145
Luminaire efficacy (lm/W)	81
Colour temperature (K)	6300
CRI (Ra)	70
Photobiological Risk Group	RG02
Luminous flux (emergency) (lm)	145
Total power consumption (W)	1.8
Electrical protection	Class II
Control gear type	Emergency (3 hour non-maintained)
Average life (Nominal) (h)	35040
Housing colour	White
IP rating	IP40
IK rating	IK03
Product EAN number	5410288417301
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0041730
Product name	SylSafe Spot RA C EM3 NM DA
Technology	LED
Type	LED
Mount	Surface mounted

SylSafe Spot

SylSafe Spot RA C EM3 NM DA

0041730

General application	Office,Hospitality,Retail,Museums & Galleries,Education
Certifications	EUNEW002
ETIM Class	EC001957

Optical data

Fixture luminous flux (lm)	145
Luminaire efficacy (lm/W)	81
Colour temperature (K)	6300
CRI (Ra)	70
Distribution type	Corridor / Area selectable
Photobiological Risk Group	RG02
Luminous flux (emergency) (lm)	145
Emergency duration (h)	3

Electrical data

Total power consumption (W)	1.8
Mains voltage (V)	230-240V~
Lamp power factor	0.44
Electrical protection	Class II
Control gear required	Yes
Control gear type	Emergency (3 hour non-maintained)
Drive current (mA)	35
kWh per 1000 hours burning time	2
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	35040
----------------------------	-------

Physical data


Housing colour	White
IP rating	IP40
IK rating	IK03
Nominal Product Length (mm)	120
Nominal Product Width (mm)	120
Nominal Product Height (mm)	44
Weight (kg)	0.246

Packaging


Single packaging type	Carton
Product EAN number	5410288417301
Packaging single length / height (cm)	14.0
Packaging single width (cm)	12.8
Packaging single depth (cm)	5.8
DUN14 (inner)	05410288417301
Units per outer package	50
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	34.8
Packaging outer depth (cm)	35.7

SylSafe Spot
SylSafe Spot RA C EM3 NM DA
0041730

PHOTOMETRY




TECHNICAL DRAWINGS




SylSafe Spot

SylSafe Spot RA C EM3 NM DA
0041730


SYLVANIA 0041730




This luminaire contains built in LED lamps.




The lamps cannot be changed in the luminaire.


874/2012 



This luminaire contains built in LED lamps.



The lamps cannot be changed in the luminaire.

SYLVANIA 0041730  874/2012