RouteLED ROUTELED 3W SURFACE OA S/TEST 9154070

Product features



 Surface mounted stand alone emergency luminare downlight with Self Test Facility. Includes Open Area lens, module (inverter) with 3.6v 4.5ah Ni-Cad batteries. 24hr recharge time. 200mA charge currrent. 1000mA discharge current. Dimensions 185mm diameter x 40mm height. Weight: 1.1kg.













PRODUCT OVERVIEW

IPC Code	9154070
Product name	ROUTELED 3W SURFACE OA S/TEST
Technology	LED
Housing	Polycarbonate
Mount	Surface Mounted
Environment	Internal
General application	Education, Hospitality, Office, Retail
Certifications	EUNEW002
Fixture luminous flux (lm)	207
Colour temperature (K)	6000
Light colour	Daylight
Beam Angle (°)	110
Total power consumption (W)	3
IP rating	IP20
Included lamp	INTEGRATED LED

DATA TABLE


General data	
IPC Code	9154070
Product name	ROUTELED 3W SURFACE OA S/TEST
Technology	LED
Housing	Polycarbonate
Mount	Surface Mounted
Environment	Internal
General application	Education, Hospitality, Office, Retail
Certifications	EUNEW002
Optical data	
Fixture luminous flux (Im)	207
Colour temperature (K)	6000
Light colour	Daylight
Adjustable chromaticity	N



RouteLED ROUTELED 3W SURFACE OA S/TEST 9154070

Beam Angle (°)	110
Emergency duration (h)	3
Electrical data	
Total power consumption (W)	3
Drive current (mA)	700
Physical data	
IP rating	IP20
Nominal Product Width (mm)	185
Weight (kg)	1.1
Packaging	
Single packaging type	Carton
Packaging single length / height (cm)	20.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	5.0
Units per outer package	1
Packaging outer length / height (cm)	20.0
Packaging outer width (cm)	20.0

TECHNICAL DRAWINGS



RouteLED ROUTELED 3W SURFACE OA S/TEST 9154070

