

SylSafe Surface Exit Signs

Wall mounted Exit Sign Arrow Down

9154118



Product features

- Wall LED emergency exit sign with epoxy coated steel enclosure with screen printed opal polycarbonate legend panel. Arrow pointing down (EC Standard). 12 x white LEDs. 230V-50Hz, 100 lumens, 4 cell 1.1Ah NiMh battery. HxWxD = 185x385x71mm.



PRODUCT OVERVIEW

IPC Code	9154118
Product name	Wall mounted Exit Sign Arrow Down
Technology	LED
Housing	Steel
Mount	Wall mounted
General application	Education, Hospitality, Office, Retail
Colour temperature (K)	4000
Light colour	Neutral White
Average life (Nominal) (h)	50000
Housing colour	White
IP rating	IP20
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	9154118
Product name	Wall mounted Exit Sign Arrow Down
Technology	LED
Housing	Steel
Mount	Wall mounted
General application	Education, Hospitality, Office, Retail

Optical data

Colour temperature (K)	4000
Light colour	Neutral White
Adjustable chromaticity	N
Emergency duration (h)	3

Lifetime data

Average life (Nominal) (h)	50000
----------------------------	-------

SylSafe Surface Exit Signs

Wall mounted Exit Sign Arrow Down

9154118

Physical data

Housing colour	White
IP rating	IP20
Nominal Product Length (mm)	385
Nominal Product Width (mm)	75
Nominal Product Height (mm)	185
Weight (kg)	3.85

Packaging

Single packaging type	Carton
Packaging single length / height (cm)	35.0
Packaging single width (cm)	21.0
Packaging single depth (cm)	40.0
Units per outer package	1
Packaging outer length / height (cm)	35.0
Packaging outer width (cm)	21.0
Packaging outer depth (cm)	40.0

TECHNICAL DRAWINGS

