

SylSafe Surface & Suspended Exit Signs

Surface LED Exit Sign Wht Arrow Down

9144466



Product features

- Suspended LED emergency exit sign arrow down (EC Standard) white finish, 15 x long life white LEDs, includes 4.8V 1.1Ah NiCd battery, charge current 200mA nominal, Recharge period: 24hrs (14hrs for 1 hour duration), 12V, IP20.



PRODUCT OVERVIEW

IPC Code	9144466
Product name	Surface LED Exit Sign Wht Arrow Down
Technology	LED
Housing	Aluminium
Mount	Suspended, Wall or Ceiling Mounted
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW002
Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
Light colour	Neutral White
Housing colour	White
IP rating	IP20

DATA TABLE

General data

IPC Code	9144466
Product name	Surface LED Exit Sign Wht Arrow Down
Technology	LED
Housing	Aluminium
Mount	Suspended, Wall or Ceiling Mounted
General application	Education,Hospitality,Office,Retail
Certifications	EUNEW002

Optical data

Luminaire efficacy (lm/W)	100
Colour temperature (K)	4000
Light colour	Neutral White
Adjustable chromaticity	N
Emergency duration (h)	3

Electrical data

Mains voltage (V)	12V
-------------------	-----

SylSafe Surface & Suspended Exit Signs

Surface LED Exit Sign Wht Arrow Down

9144466

Transformer required Yes

Physical data

Housing colour	White
IP rating	IP20
Nominal Product Length (mm)	300
Nominal Product Width (mm)	50
Nominal Product Height (mm)	220
Weight (kg)	3.0

Packaging

Single packaging type	Carton
Packaging single length / height (cm)	30.0
Packaging single width (cm)	23.0
Packaging single depth (cm)	5.0
Units per outer package	1
Packaging outer length / height (cm)	30.0
Packaging outer width (cm)	23.0
Packaging outer depth (cm)	5.0

TECHNICAL DRAWINGS

